




## Multi-Purpose Caddys for Dishes, glasses, cups, saucers & trays



- T-190 enclosed model
- T-195 open model
- TH-190 enclosed model (heated)



TH-190  
Shown

### General Specifications

Multi-Purpose Caddy to be Caddy Corporation model T-\_\_\_\_\_.

Unit to be constructed of 16 gauge stainless steel with rounded covered corner interior and 18 gauge stainless steel undershelf for empty tray and rack storage. Frame to be 1" O.D. 16 gauge stainless steel tubing and fitted with 4" diameter heavy-duty swivel type casters with 3/4" stems and polyurethane tires. Stainless steel spacers to be between tubular frame and body to eliminate dirt pockets. Front and back to have continuous neoprene bumpers set into stainless steel channel frames. All stainless steel to be type 304 with No. 4 finish and be all welded construction.

### Enclosed Model Specifications:

Multi-Purpose Caddy for sanitary storage, to be fitted with folding covers of 1/8" thick fiberglass reinforced plastic, fastened with 16 gauge stainless steel hinges. Covers furnished with self-operating positive locking clips. Covers shall not protrude beyond frame of unit when in open position.

### Heated Model Specifications:

Heating element to be 1 KW, mounted under storage compartment. Heating element and wiring to be completely concealed. Electrical control box to be stainless steel and installed for easy removal for servicing. Control box to include infinite Hi-Lo heat control for temperature settings 1 through 9 and a recessed male three-pronged NEMA twist-lock receptacle. Unit to be supplied with a 6'-0" long cord with a NEMA twist-lock female connector.

Unit to be provided with the following accessories:

### Accessories

- ACC-38** - Circular bumpers. (Add 4" to length and width)

| Dimensions              |                                  |                                  |                                  |
|-------------------------|----------------------------------|----------------------------------|----------------------------------|
| Model                   | Length                           | Width                            | Height                           |
| T-190, T-195,<br>TH-190 | 39 <sup>3</sup> / <sub>4</sub> " | 27 <sup>1</sup> / <sub>4</sub> " | 40 <sup>3</sup> / <sub>4</sub> " |


| Electrical Data |       |   | NEMA |       |          |
|-----------------|-------|---|------|-------|----------|
| Model           | Volts | φ | Amps | Plug  | Outlet** |
| TH-190          | 120   | 1 | 8.3  | 5-15P | 5-15R    |
|                 | 208   |   | 4.8  | 5-15P | 5-15R    |
|                 | 240   |   | 4.1  | 5-15P | 5-15R    |

\*\* Outlet not supplied by Caddy Corporation.


Heated units only to be certified by Intertek.



### Multi-Purpose Caddy Capacities\*\*\*




Cups:




Dishes:

- 300 10" plates
- 300 9" plates
- 600 7" plates
- 750 6" plates



Cups & Saucers:  
126 cups in 20" x 20" racks  
and 126 saucers



Trays:

160 trays up to 18" x 22"



Cups or Glasses:  
120 cups or 216 glasses in  
10" x 20" racks

\*\*\* Actual capacities vary with shape of object to be dispensed.



\* Not available with model TH-190