

QuietQube® RNF-2000C

Remote Nugget Ice Machine

Models – 60Hz	N /						\sim		
	1\/	$I \cap C$	Р	15	_	h	()	Н	7

☑ RNF-2000C



RNF-2000C Remote Nugget Ice Machine



RCUF-2200C Condensing Unit



RNF-2000C Remote Nugget Ice Machine on D570 Bin

Project ______

Item _____

Quantity _____

CSI Section 11400

Approved ______

Date _____

QuietQube® Series Remote System consists of a remote condensing unit, interconnecting refrigerant lines, ice machine head section, and ice storage unit-All ordered separately. QuietQube ice machine with RCUF condensing unit is designed as a Manitowoc system and not for use with any other ice machine or remote condenser brand.

- Up to 1,915 lbs (868 kg) daily ice production.
- Only 30" (76.2 cm) wide.
- Evaporator is designed for maximum quality and operating life.
- Remote, air-cooled condenser system improves efficiency and ice production, conserving energy. Manitowoc remote condenser systems effectively dissipate heat at a convenient location, indoors or outdoors, away from the ice machine. This maximizes icemaking capability and minimizes air conditioning loads by lowering the ambient air temperature at the ice machine.
- Quiet operation eliminates most noise from the refrigeration system. Promotes a relaxing atmosphere.
- Ice machine is lighter in weight to simplify installation.
- Stainless steel exterior has a clean and modern look to enhance the display in any self-serve environment.



Ice Shape

Nugget ice consists of small pieces ranging from 3/8" to 1/2" in width and length. Offers a 85% ice to water ratio with a soft, chewable texture while still providing maximum cooling and great dispensability.




Ice shown actual size










Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com 7249 10/19










Bin	Adapter
D-970	K-00470
F-1325/1650	K-603030
FC-1350	K-613030

Water-Cooled Unit Option:
(B) 3/8" F.P.T. Condenser Inlet
(C) 1/2" M.P.T. Condenser Drain
(D) 1/2" M.P.T. Ice Making Water Drain
(E) 3/8" F.P.T. Ice Making Water Inlet

F) 3/4" F.P.T. Bin Drain

RCUF-2200 Condensing Unit



Condensing Unit Electric

208-230/60/3 standard.

Note: QuietQube ice machine is wired independent of

condensing unit.

Min. circuit ampacity: 15 3ph
Max. fuse size: 15 3ph
BTU Per Hour: 15,700 (average)
Compressor: Nominal rating: 3 HP

Operating Limits:

Ambient Temperature Range: -20° to 120°F (-29° to 49°C)

Installation Information and Dimensions:

Maximum Line Length—100' (30.5 m)*

Maximum Vertical Rise*—35' (10.7 m) above ice machine.

Maximum Vertical Drop—15' (4.5 m) below ice machine.

*A rise over 20' (6 m) requires S-Trap Kit K-00172 - ordered

separately

Standard Interconnecting Tubing

	Line Length		Weight		
Model	ft.	m.	lbs.	kgs	
RC-51	50	15.2	27	12	

Remote Air-cooled Ice Machine

	Ice Shape	Ice Production 24 Hours		Power Usage	Potable Water Usage	
Model		70°Air/ 50°F Water 21°Air/10°C Water	90°Air/ 70°F Water 32°Air/21°C Water	90°Air/ 70°F Water 32°Air/21°C Water	/100 lbs. 45.4 kgs. of Ice	
RNF-2000C	Nugget	1915 lbs.	1475 lbs.	4.42	12 Gal.	
		868 kgs	669 kgs	4.42	45 L	

Order ice storage bin separately. Will not accept AuCS accessory. **Note:** Use K00488 ice level management kit on disperser applications

Welbilt reserves the right to make changes to the design or specifications without prior notice.

