Merchandiser Freezer Swing Door Series



FMD-23F ltem # _____

Standard Features

- Glass Door Merchandisers are designed with quality and durability that you will not find in any other products in its class.
- No-chip exterior, durable and stylish black vinyl finish Std.
- Easy to clean NSF approved white coated steel interior, Stainless steel floor.
- Electronic controller for a proper temperature thru out your box.
- "Low-E" consumption **LED interior lighting** provides greater visibility, shadow-free illumination and enhanced product display.
- With innovative and eco-friendly technology, Fagor utilizes R-290 Hydrocarbon designed to meet DOE's Energy Conservation standards with very low contribution to global warming (ODP-0) (GWP-3).
- On & Off door rocker switch which reduces the amount of moisture and helps preserve temperature inside the cabinet.
- High density, CFC-Free polyurethane insulation.
- "Low-E" triple pane thermal insulated glass door with extruded aluminum frames for the best efficiency and durability.
- High/low temperature alarm and automatic defrost.
- Adjustable epoxy coated wire shelves (four per door standard).
- Bottom mount compressor system with service friendly rail system.
- Illuminated exterior sign panel.
- NSF-7 listed for storage and/or display of packaged or bottle products.



FMD-23F

Options & Accessories

- Epoxy coated shelves
- 3" castors
- 220 volts / 50 cycles / 1 phase















*Conforms to UL & NSF-7 standards

ezer	Model	Doors	Capacity Cu. Ft.	Shelves	Amps	HP	Volt	NEMA Plug	Cord Length	Cabinet Dimensions W/D/H			Shipping (Wt. Cubes)	
Fe	FMD-23F	1	23	4	4.3	1/2	115	5-15P	8'	27"	32"	78-5/8"	262	47

Merchandiser Freezer Swing Door Series



Specifications

Construction

Exterior made of durable stylish black vinyl on steel, non-chip or peel. White coated steel interior, NSF approved with high quality stainless steel floor. High density and environmentally friendly CFC-Free polyurethane insulation.

Entire cabinet is foamed in place. Triple pane thermal insulated glass door with extruded aluminum frames for the best efficiency. Self-closing doors with magnetic gaskets, positive seal closure system and aluminum handles.

On & Off door rocker switch.

Low energy consumption LED interior lighting, full height along the door frame including a safety shield per section outside the food zone.

Refrigeration System

Factory oversized and balanced refrigeration system, using environmentally friendly (CFC Free) R-290 refrigerant. Bottom mounted condensing unit on a rail system. Evaporator coil is mounted to interior top panel. Large fan motor and fan blades for better air flow. Freezer maintains an optimal temperature of -10°F.

Precise electronic controller. Automatic

FMD-23F

defrost and temperature door alarm.

Shelving


Four epoxy coated wire shelves with clips per door. Adjustable in-1/2"increments. Aluminum pilasters with stainless steel clips.


Others


Unit is supplied standard with a 8' cord and plug (Nema 5-15p).

Warranty

3 year parts and labor warranty plus 2 additional year compressor warranty. (Continental U.S.A. & Canada only).







The manufacturer reserves the rights to modify materials and specifications without notice $\frac{1}{2}$