

{13.56}



Adjustable Slide Aluminum Pan Racks

Adjustable slide pan racks are built for tough applications and hold a variety of items of different sizes. Adjustable slides accommodate all popular modules used in the foodservice industry. Heavy-duty extrusion (.1" or 2.5mm thick) with bending support design for heavy loads.

Features & Benefits:

- **Material:** Natural finish, high-strength, extruded aluminum (6063-T6 alloy).
- **Rugged:** Aircraft-riveted construction throughout provides additional strength. Reinforced corner angles.
- **Adjustable Slides:** Keyholes in uprights on 1.5" (38mm) spacing. Ideal for holding a variety of items of different sizes at different times.
- **Pass-Thru Design:** Can be loaded on one side and unloaded from the other for maximum efficiency and convenience.
- **RD78N (13 Sets of Adjustable Slides)**
RF78N (12 Sets of Adjustable Slides): Accommodate most pans used in the foodservice industry. Made of special extrusion (.100" or 2.5 mm thick) with bending support design for heavy loads.
- **Transport or Storage**
- **Refrigerator or Freezer**



RD78N
(69.5" Tall / 13 Slide Sets)



RF78N
(Roll-in Refrigerator 63.5" Tall / 12 Slide Sets)



{13.56} Adjustable Slide Aluminum Pan Racks



Specifications:

- **Material:** Special design, natural finish, high-strength, extruded 1/8" (3.1mm) thick aluminum (6063-T6 alloy).
- **Construction:** Pass-thru design, aircraft-riveted construction throughout. Keyholes in uprights on 1.5" (38mm) spacing. Inside height is 60.25" (1530mm).
- **Top & Bottom:** 1.5" x 1.5" x .125" (38 x 38 x 3.1mm) angle-shape riveted to four corner posts. Closed bottom.
- **Corner Posts:** 1.5" x 1.5" x .125" (38 x 38 x 3.1mm) angle-shape.
- **Slides:** 3" x 4.5" x .100" (76 x 114 x 2.5mm) extruded adjustable slides, with top, center and bottom slides riveted in place, remaining sets adjustable on minimum 3" (76mm) centers. .5" (12mm) diameter stabilizer rod positioned at center, front and back. 12 sets of RF78N, 13 sets of RD78N, adjustable on 1.5" centers, 3" minimum slide spacing.
- **Casters:** Two 5" (127mm) double ball bearing swivel, ball bearing axle, nickel-plated, donut neoprene-tired, pre-lubricated, bolted through separate full-length, angle-formed, .125" (3.1mm) thick aluminum plates to bottom of chassis. Two with wheel brake.

Pan Capacity with (13) Standard Sets of Slides on 4.5" (114mm) Centers*

No. Pans	2 Per Slide Size		No. Pans	1 Per Slide Size		Approx. Pkd. Wt.		Cat. No.
	(in.)	(mm)		(in.)	(mm)	(lbs.)	(kg)	
26	10.83x19.75	275x502	13	15x20	380x520	93	41.8	RD78N
26	11.13x20	284x508	13	18x26	457x660			
26	12x18	304x457	13	20x20	508x508			
26	12x20	304x508	13	20x22	508x558			
26	13x18	330x457	13	20x24	508x610			
26	14x18	335x457						

*Vertical supports punched on 1.5" (38mm) centers for adjustability. Note: 5" (127mm) heavy-duty swivel casters with neoprene wheels, two with brakes, are standard on unit listed above. Notes: Accessories must be ordered with rack. Not designed for field installation. Accessorized racks shipped assembled. Part numbers will be combined to signify complete unit at time of order entry. Weight Load Capacity: 50 lbs. (22.7kg) per slide level; 350 lbs. (159kg) per rack. Allowable temperature range: -30°F (-34°C) to 160°F (71°C).

Pan Capacity with (12) Standard Sets of Slides on 4.5" (114mm) Centers*

No. Pans	2 Per Slide Size		No. Pans	1 Per Slide Size		Approx. Pkd. Wt.		Cat. No.
	(in.)	(mm)		(in.)	(mm)	(lbs.)	(kg)	
24	10.88x19.75	275x502	12	15x20	380x520	92	41.4	RF78N
24	11.13x20	284x508	12	18x26	457x660			
24	12x18	304x457	12	20x20	508x508			
24	12x20	304x508	12	20x22	508x558			
24	13x18	330x457	12	20x24	508x610			
24	14x18	335x457						

*Vertical supports punched on 1.5" (38mm) centers for adjustability. Note: 5" (127mm) swivel casters, two with brakes, are standard on units listed above. Weight Load Capacity: 20 lbs. (9kg) per slide level; 350 lbs. (159kg) per rack. Allowable temperature range: -30°F (-34°C) to 160°F (71°C).

Accessories

Description	Cat. No.
Gray Continuous Bumper*	A33RD
Gray Corner Bumpers**	A37
Floor Lock	A71
Extra Slides	A121

*Adds 2" (51mm) to overall width and depth of rack.

**Adds .5" (12.7mm) to overall width and 1" (25mm) to overall depth of rack.

Notes: Accessories must be ordered with rack. Not designed for field installation. Accessorized racks shipped assembled. Part numbers will be combined to signify complete unit at time of order entry (ex. RD78NA120 or RD78NA33A120).

{13.56}



Adjustable Slide Aluminum Pan Racks

