



## **PRODUCT SPECIFICATION**

### **Transportation Cart**

Model #: HD-RTC

UPDATED: November 2005

### **General Construction**

Transport cart shall be a completely welded assembly. Casters shall be bolted to cart base cross mounts. The cart shall have two vertical support railings to allow for round or rectangular tables to "lean" against for maintaining tables within cart base. The railings shall be affixed to the outside frame brace. Railings shall be 38" wide and 42" high from floor to railing top. Railings shall be removable to accommodate any number of storage configurations. Cart shall be finished with an epoxy powder coating. The color shall be Black.

### **Capacities**

8-10 round tables (48", 60", 66", 72") stacked vertically.

10 rectangular tables (18"x72", 24"x72", 30"x72", 36"x72") stacked vertically (2.875" width).

### **Dimensions**

Overall dimensions shall be 38.5"L x 32.75"W x 42.0"H. Transport cart base dimensions shall be the same.

### **Cart base frame construction**

Outside frame brace: (2) 14 gauge – 1 x 2 rectangle steel channels

Lateral frame brace: (4) 14 gauge x 1.25" tubular steel braces

End handle/swivel caster frame brace: (2) double rail receptacles to accommodate single rail/handle post at each cart corner shall be 1 9/16" OD, 10 gauge round steel tubing

Caster mounts: Caster top shall be bolted directly to lateral frame base.

Cart railings: 1 x 2 rectangular, 16 gauge steel tubing.

### **Standard Casters**

Castors shall be weight rated to hold 325 pounds each / 1300 pounds per cart. Standard castors shall be (4) 5" diameter x 1" width high-density polypropylene swivel. Castors will be bolted to caster mount plates by grade 8, 3/8"-16x3/4" bolts with 3/8"-16 lock nuts. 6 inch caster option available for small incremental charge

### **Warranty**

Palmer Snyder warrants that all transportation carts will be new and manufactured with quality materials and workmanship. Palmer Snyder further agrees to replace promptly any part or parts which by reason of defective material or workmanship shall fail under normal use for a period of 5 years from date of acceptance. Warranty for rental companies is 1 year. All warranty issues are subject to management approval and are deemed prorated.