

# ASPIRAL MIXERP



Spiral Mixer, 88 Lb. Dough Capacity, 2 Speeds, Programmable Digital Control, Stationary Stainless Steel Bowl, Safety Guard & Dough Hook, Cast Iron Frame with Enamel Coated Steel Finish, 4 HP, 208-240/60/1P/10A, NEMA 6-20P



PROJECT	
ITEM NO.	
NOTES	

MODEL NUMBER: A E F 0 2 5 S P



#### **FEATURES**

- ☐ Unique Easy to Use Digital Control
  - 2 Speeds (no need to stop mixer to change speed)
  - 99 Minute Mixing Timer
  - 9 Programmable Speed & Time Settings
- **Emergency Stop**
- Stainless Steel 54 Quart Bowl with Rounded Center Post
- Stainless Steel Dough Hook
- Integrated Standard Bowl Drain
- Wire Guard for Bowl Featuring Automatic Motor Cut-Off Switch
- Thermal Overload Protection for Motor
- Non-Slipping Belt Driven Motor

#### **CONSTRUCTION**

- ☐ Heavy Duty Frame with Lead-Free Enamel Coating
- S/S Legs to Prevent Rusting
- Carbon Steel Frame

#### **OPTIONS & ACCESSORIES**

- Stainless Steel Construction [Suffix I]
- Paddle w/Scraper (Installed by Factory) [AEF025P & AEF025S]
- #12 Hub Attachment [uses BTF accessories]

#### **CLEARANCES**

- ☐ 6" (152mm) On All Sides
- ☐ Top & Bottom Must Remain Unobstructed
- □ Note Additional Clearance Requirements if Utilizing #12 Hub Attachments

#### **WARRANTY**

☐ One Year Labor & Two Year Parts

c LISTED US	AND THE STATE OF T
Intertek	Intertek

	11/-1-11	Overall Dimensions			24-1115		Dough Capacity
Model	Weight	w	D	н	Motor HP	Hub	(60% AR)
A 550355D	980	18.89"	32.08"	45.47"	4	YES	88 lbs
AEF025SP	(445)	(480)	(815)	(1155)			(40 kg)
					•		

	Electrical System						
Model	Volts	Amps	Phase	Hz	kW	NEMA	
AFFORES	208	16	1	F0/60	2	6-20P	
AEF025SP	240	16	1	50/60	3	6-2UP	
















**KCL & REVIT DRAWINGS UPON REQUEST** 




PROJECT	
ITEM NO.	
NOTES	

MODEL NUMBER: A E F 0 2 5 S P

## **DRAWINGS**





# **Capacity Chart**

Recipe/Product	Pounds	Kilograms	
Flour Capacity Minimum	5	2	
Flour Capacity Maximum	55	25	
50% AR Dough Minimum	5	2	
50% AR Dough Maximum	50	25	
55% AR Dough Minimum	5	2	
55% AR Dough Maximum	60	27	
60% AR Dough Minimum	8	3.5	
60% AR Dough Maximum	88	40	
65% AR Dough Minimum	3.3	1.5	
65% AR Dough Maximum	44	20	

### Calculating AR%

To know the absorption ratio of your recipe use the following formula:

%AR = Water Weight (lbs) / Flour Weight (lbs)

1 Canadian Gallon of Water = 10lbs (4.54 kg)

1 US Gallon of Water = 8.33lbs (3.77kg)

Use of ice requires a 10% reduction in batch size. Drop 10% from the above chart for high gluten flour.

Make sure to take into consideration all water content. This should include any extracts, butter/shortening, eggs, etc. into factoring AR%.

For Example: Your using 1 US Gallon of water and 15lbs of flour = 0.55 or 55% AR

That means you will have a finished product of 23.3lbs of dough at 55% AR. Refer to this chart to find the model you will need.

Doyon/NU-VU recommends the following capacity ratings on based AR%. If dough has a lower AR% we recommend decreasing the recipe to adjust for denser dough. Failure to follow said guidelines or recommendations could result in non-warrantied service issues with mixer.

Please contact factory to verify if mixer is suitable for your application.

**Note** - Different Types of flour have different gluten content and are not universal between products.

Note - Eggs, Milk, Extracts, must be added to liquid when calculating AR%

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While Doyon exercises good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using these specifications. By using the information provided, the user assumes all risks in connection with such use.









**REVISION C | 5/14/2021**