



Outperform every day.™

Project:

Item Number:

Quantity:

LIDSAVER™ IN-COUNTER SINGLE LID DISPENSERS



DESCRIPTION

The LidSaver™ single lid dispenser patented design reduces lid waste by dispensing one lid at a time, and by making it easy to identify the correct lid size. Customers retrieve a lid with one hand without touching other lids in the stack, which helps keep lids sanitary.

FEATURES

- In-counter installation
- Configurable to dispense a variety lid types - cold drink, hot drink, tabbed, domed, contoured, slotted, gourmet coffee, soup cup; in lid sizes from 2¾" - 4¾" (7 - 12.1 CM)
- Meets Federal Mandate #4-904.11
- Rugged thermoplastic housing
- Anti-microbial labels

ACCESSORIES

- ☐ **Retro-Fit Kit** - Reconfigure LidSaver™ to dispense a different lid type or size. For details visit www.vollrath.com.
- ☐ **Tune-Up Kit** - Return LidSaver™ to like new performance levels by realigning components. For details visit www.vollrath.com.

Agency Listings



Due to continued product improvement, please consult www.vollrath.com for current product specifications.

HOW TO ORDER

Step 1 Select a LidSaver™ Type		Step 2 Select Lid Component
Description	Model Number	Refer to the In-Counter Installation Lid Code Matrix below.
Horizontal. 23" (58.4 cm) Clear faceplate, clear door.	LS01	
Vertical. 23" (58.4 cm) Clear faceplate, clear door.	LS01V	
Horizontal. 23" (58.4 cm) Clear faceplate, clear door.	LS01	
Vertical. 23" (58.4 cm) Black faceplate, clear door.	LS01VB	
Horizontal. 18" (45.7 cm) Clear faceplate, clear door.	LS01S18	
Horizontal. 18" (45.7 cm) Black faceplate, clear door.	LS01S18B	

Your Selection -

EXAMPLE	LS01	-	AB	=	LS01-AB
----------------	------	---	----	---	---------

Lid Code Matrix			
Manufacturer Part No.	Code	Manufacturer Part No.	Code
Berry™ DLT1310 Domed	AB	Dart® 32SLR	AQ
Berry™ DLT1310SS	AC	Dixie® 9542	AR
Berry™ DLT1402 Domed	AD	Dixie® 955	JY
Berry™ DLT1402SS	AE	Dixie® TP9542	AS
Berry™ DLT1408 Domed	AF	Dixie® TP9550	JZ
Berry™ DLT1408SS	AG	International Paper LCRS 32	AT
Dart® 16EL	AJ	International Paper LCTS 44	AU
Dart® 16LCDH	AK	Sweetheart® LGX12R	AY
Dart® 16RCL	AL	Solo® 626	AZ
Dart® 16SL	AM	Solo® DL626	BB
Dart® 20SL	AN	Solo® DLR642	BC
Dart® 20SLR	AO	Solo® LD16A	BD
Dart® 32SL	AP		

Additional lids are available. Find the full Dispenser Code Lookup Tables file at www.vollrath.com/Dispenser-Item-Builder.htm

Dart, Solo and Sweetheart are registered trademarks of Dart Container Corporation. Berry is a trademark of Berry Plastics Corporation. Dixie is a registered trademark of Georgia-Pacific. International Paper is a registered trademark of International Paper.

NOTE: LidSaver™ items are custom products and are non-returnable.

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to the Vollrath Equipment and Smallwares Catalog.

Approvals	Date



Outperform every day.™
www.vollrath.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53081-3201 U.S.A.
Customer Service: 800.628.0830
Canada Customer Service: 800.695.8560
Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832
Technical Services Fax: 920.459.5462

LIDSAVER™ IN-COUNTER SINGLE LID DISPENSERS**DIMENSIONS**

Face: 6 $\frac{7}{8}$ x 6 $\frac{1}{2}$ (17.5 x 16.5)

Housing extension from counter: 2 (5.1)

From counter face to counter interior: 23 (58.4) or 18" (45.7 cm)

Tube Diameter: 6 x 5 $\frac{1}{4}$ (15.5 x 13.3)

Cutout: 6 $\frac{3}{16}$ x 5 $\frac{7}{16}$ (15.7 x 13.8)

IMPORTANT: When LidSaver™ is mounted above a lateral surface (such as a shelf extending straight out from the counter face) it needs to be mounted so that the bottom of the housing is $\frac{3}{4}$ " (1.9) above this surface. The bottom of the hole cut-out should be 1 $\frac{1}{4}$ " (3.2) above this surface. This is necessary to allow sufficient clearance for the housing to be removed when necessary.



Outperform every day.™

www.vollrath.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53081-3201 U.S.A.
Customer Service: 800.628.0830
Canada Customer Service: 800.695.8560
Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832
Technical Services Fax: 920.459.5462