

Universal Guide Roll-In Racks

JOB_____ ITEM # _____ QTY # ____

MODEL NUMBER

- DXPRIU6912
- DXPRIU6411
- □ DXPRIU5810



DXPRIU6411 Shown with optional solid bottom and wrap-around bumper



Series DXPRIU aluminum universal guide, open roll-in racks to accommodate 18" x 26" sheet pans or 12" x 20" food pans, for use in refrigerators and freezers.

FRAME

The vertical uprights and the top and bottom cross bracing are 2" x 1" x 1/8" thick extruded aluminum channels, welded to form a rigid frame. Each vertical upright is fabricated with a series of obtuse angle slots, 1-5/8" on centers, to receive and contain the guides. Caster support channels are 1-7/8" x 4" x 1/8" thick extruded aluminum, fully welded to the vertical uprights and bottom cross supports.

GUIDES

The two level guides are $1/2" \times 1" \times 7/8" \times 3-1/8" \times .105"$ thick extruded aluminum, with all corners chamfered and deburred. They are easily removable and are securely held in position by a series of obtuse angle slots, 1-5/8" on center, which are punched in one wall of each channel upright.

TIE ROD

All models have 1/2" diameter aluminum tie rods welded to the front and rear vertical uprights for extra rigidity.

CASTERS

The units are mounted on four 5" diameter, heavy duty, swivel casters.

DIMENSIONS

MODEL NO.	DIMENSIONS W-D-H	SPACING O.C.	PAN CAPACITY		VA/T
			18"x26"	12"x20"	WT.
DXPRIU6912	23-3/4" x 26" x 69"	4-7/8"	12	24	90
DXPRIU6411	23-3/4" x 26" x 64-1/2"	4-7/8"	11	22	85
DXPRIU5810	23-3/4" x 26" x 58-1/2"	4-7/8"	10	20	80

NOTE: Before ordering Roll-In rack, be sure to verify the clear opening provided in the refrigerator or freezer being used with the Roll-In rack.

For lugs, trays or other size pans, apply to factory for dimensions and capacities.

RACKS OPTIONS / ACCESSORIES PART NUMBER

Option	Description	
DXPPS	Pan Stop	
DXPEMB	Personalized Embossment (12 letters per line)	
DXPFL	Floor Lock	
DXPPH	Push Handle	
DXPY5	5" Polyurethane Casters (set of 4)	
DXPB	Non-Marking Rubber Bumpers - Corner (set of 4)	
DXPPB	Non-Marking Rubber Bumpers - Full Perimeter	
DXPWB	Wheel Brakes (set of 2)	
DXP52	Heavy-duty Casters (set of 4)	
DXPV	Vertical Bumpers	
DXPSB	Solid Bottom	

SPEC

I-10

LIMITED WARRANTY: DINEX warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.



4711 E. Hefner Road Oklahoma City, OK 73131 800.654.8210 405.475.5600

We do not accept returns on any Dinex equipment or Dinex custom products. Please contact your local Dinex rep to ensure order accuracy prior to ordering.