

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

# Pass Thru Half Solid Door Heated Cabinet

Pass-Thru PRO Series

Model: PRO-50-4H-PT(-AL)(-AR)

### \_\_\_ FEATURES & BENEFITS =\_\_

#### ■ Digital temperature control & monitor system

- Keeps food products safe by maintaining constant temperatures
- · Alarm beeps when doors are not sealed
- Early warning alarm program detects issues before malfunction occurs
- · Digital display allows for easy monitoring
- · Sensitive touch display

#### ■ Ducted fan air distribution system

Maintains temperature within the food zone

#### On/Off switch

ON/OFF switch is located on control panel

#### All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

#### Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

#### ■ LED interior lighting

#### ■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Half length stainless steel solid doors with locks
- Self-closing doors with stay open feature at 120 degrees
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles

• PRO-50-4H-PT: Standard hinged • PRO-50-4H-PT-AL: All Left hinged • PRO-50-4H-PT-AR: All Right hinged
















(unit: inch)

# Model: PRO-50-4H-PT(-AL)(-AR)

ELECTRICAL DATA		
Voltage	208~230V/115V/60Hz/1Ph	
Plug Type	NEMA L14-20P	
Full Load Amperes	15	
Wattage (W)	3000	
Cord Length (ft.)	8	
DIMENSIONAL DATA		
# of Doors	8	
# of Racks Accepted	2	
Net Capacity (cu. ft.)	48.7	
Ext. Length Overall (in.)	513/4 (1314mm)	
Ext. Depth Overall (in.)*	361/4 (920mm)	
Ext. Height Overall (in.)†	78 (1982mm)	
Int. Length Overall (in.)	421/4 (1073mm)	
Int. Depth Overall (in.)	275/8 (702mm)	
Int. Height Overall (in.)	583/4 (1493mm)	
# of Shelves	6	
Shelf Size (L x D) (in.)	223/4 x 263/8	
Net Weight (lbs.)	452	
Gross Weight (lbs.)	510	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

#### ■ WARRANTY: 3 Year Parts and Labor Warranty


#### STANDARD FEATURES


- Door locks
- 4" dia. swivel casters with locks on the front set
- Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design

#### **OPTIONAL ACCESSORIES**

- 5" caster, 1/2" diameter & 13 TPI:
- M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: (L, R) H50R901700
- Tray slides kits: TS23-N1LR(#1), TS23-N1LR HALF, TS23-N4LR(#4), TS23-N4LR HALF, TS23-UNLR(Universal), TS23-UNLR HALF

## PLAN VIEW





Ver.20230608











■ Turbo Air: 800-627-0032 ■ GK: 800-500-3519













<sup>\*</sup> Depth does not include 2-1/4" for door handles.

<sup>†</sup> Height does not include 5" for caster height.