APPLICATION:		PRODUCT NAME:	SP
		SINGLE DECK CONTROL VALVE	<u>=C. 5</u> (
JOB NAME:		SPECIAL CONFIGURATION  CHECK BASE MODEL AND OPTIONS	SPEC. 5000 REV."B"
QUANTITY:	ITEM NO.	MODEL:	<u> </u>
		□ 5000	٣
2-1/2" [63.5mm]  5" [127mm]  MALE  ROUGH-IN:	4-1/2" — [114.3mm]  1-7/8" [47.6mm]  Ø2-1/2" [63.5mm]	OPTIONS OR MODIFICATIONS:  VANDAL RESISTANT KIT  HANDLES (CROSS OR WRIST) CIRCLE STYLE  OTHER  FEATURES  CONTROL VALVE * SINGLE DECK * STEM - LEFT HAND * HOT AND COLD INDEX BUTTONS * SWIVELLING SEAT DISK * STAINLESS STEEL SEAT * STAINLESS STEEL SEAT * STAINLESS STEEL SEAT SCREW  RECOMMENDED SETTINGS * 110°F AT 80 PSI  SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC * 29 GPM @ 80 PSI  SHIPPING WEIGHT * XXX.XX LBS	
+	Ø1-3/16" [30.16mm]	FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238	_
<b>(F)</b> ANSI/A112.18.1M		information@fisher-mfg.com - www.fisher-mfg.com	