



POWER PACK - WATER COOLED

PREMIUM - 2 PUMP - 5,100 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.




Reverse side showing water connections.



MMPP4303-PKG-WC

Water Cooled:

Designed for spaces with limited air circulation or high ambient temperature.



6-20P*



*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.



Part No.	Description	Shipping Weight
<input type="checkbox"/> MMPP4303-PKG-WC	Water cooled power pack, 2 pump and motor	80 kg 175 lbs

Operating Performance

Compressor	3/4 HP	Condenser Inlet Water Temp	Minimum 45° F / Maximum 80° F
BTU per hour	5,100	Pump Type	Rotary Vane
Plug Type (NEMA #)	6-20P*	Push In Connector	12.7mm (1/2") O.D.
Cord Length	8'	Water Inlet & Outlet Fitting	Female 3/8" NPT
Voltage	208/230	Minimum Water Pipe Size	3/8"
Running	8.4A	Inlet Water Pressure	Minimum 40 psi / Maximum 120 psi
Refrigerant	R-134a	Water Usage	.3 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
Charge	0.51 kg (18 oz)		
Refrigerant Running Pressure	18 (low) 140 (high)		
Bath Capacity	43.5 litre (11.5 Gallons)		

*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.

Dimensions

