



BEVERAGE-AIR®

| | |
|-----------------|------|
| Project: _____ | AIA# |
| Item: _____ | |
| Location: _____ | SIS# |
| Approved: _____ | |

CT1HC TOP MOUNT CROSS TEMP®

TOP MOUNTED CROSS TEMP®

CT1HC Half-Glass Door Variable Speed Freezer/Refrigerator Hydrocarbon Series

MODEL:
CT1HC-1HG



7 Year Parts/Labor Warranty
7 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior is stainless steel front with continuous coil coated sides
- Interior liner is made of corrosion resistant aluminum
- Expansion valve technology
- Easily converts from refrigerator to freezer
- Single cabinet configurable to all menu initiatives, temperature range of -15 to 40° F
- Modulates coil temp to achieve desired set point
- Intuitive compressor
- Quicker pull-down
- Improved product stability
- Rapid recovery defrost
- Three (3) epoxy coated shelves
- Field-reversible doors
- 6" Casters with (2) brakes

OPTIONS & ACCESSORIES

- Stainless steel exterior
- Stainless steel interior
- Stainless steel tray (A)
- Universal tray slide (AC)
- Epoxy coated wire rod tray slide (kit #4)
- Door locks
- Additional shelves
- Left hand hinged
- 3" Casters
- 6" Flanged legs

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Variable speed compressor technology achieve 30% more energy efficiency
- Adaptive defrost
- Epoxy coated evaporator coil




Please verify qualifying units by visiting:
www.energystar.gov/cfs

3779 Champion Blvd., Winston-Salem, NC 27105
1-888-845-9800 Fax: 1-336-245-6453
Beverage-Air.com Sales@bevair.com



BEVERAGE-AIR®

Cross Temp® Top Mount Freezer/Refrigerator Model: CT1HC-1HG

| MODEL | CT1HC-1HG |
|----------------------------------|--------------------|
| EXTERNAL DIMENSIONAL DATA | |
| Width Overall | 26" |
| Depth Overall with Handles | 33 5/8" |
| Height Overall | 85" |
| Number of Doors | 2 |
| Depth with Door Open 90° | 55 1/8" |
| Door Openings (in) | 21 5/8" x 29 5/8" |
| INTERNAL DIMENSIONAL DATA | |
| NET Capacity (cubic ft.) | 23.1 |
| Internal Width Overall (in) | 22 7/8" |
| Internal Depth Overall (in) | 26 1/8" |
| Internal Height Overall (in) | 62" |
| Number of Shelves | 3 |
| ELECTRICAL DATA | |
| Full Load Amperes 115/60/1* | 8.0 |
| REFRIGERATION DATA | |
| Horsepower | 4/5 |
| Capacity (BTU/Hr) | 1970-4950 |
| Heat Rejection (BTU/Hr) | 2955-7425 |
| Charge (lbs/grams/ounces) | 0.286 / 130 / 4.58 |
| SHIPPING DATA | |
| Gross Weight - Crated | 364 lbs |
| Height - Crated | 88" |
| Width - Crated | 41" |
| Depth - Crated | 33" |

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

ELECTRICAL CONNECTION



**115/60/1*
NEMA 5-15P**

Unit pre-wired at factory and include 8' long cord and plug set.

* NOTE: Units that utilize variable speed compressor technology can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Beverage-Air recommends using either an Eaton, SCF20, or HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

Model Views

Required Clearance: Top 12", Rear 3"

PLAN VIEW

ELEVATION VIEW

SIDE VIEW

