



O8600 Series EXTRUDED SIDE PANEL TRAY RACKS

Standard and Wide Opening Racks for 18"x26" Trays

CARTER-HOFFMANN



FOOD SERVICE EQUIPMENT
EXTRUDED SIDE PANEL RACKS

SPECIFICATIONS

Printed in U.S.A. 125 0809
Carter-Hoffmann is a trademark
of Carter-Hoffmann LLC

| Model Number | Tray Capacity | Tray Slide Spacing | | Overall Dimensions | | | | | | Caster Diameter | | Shipping Weight | |
|--|---------------|--------------------|----|--------------------|------|--------|-----|--------|------|-----------------|-----|-----------------|-----|
| | | | | Height | | Depth | | Width | | | | | |
| | 18"x26" | in | mm | in | mm | in | mm | in | mm | in | mm | lbs | kgs |
| <input type="checkbox"/> O8619 | 19 | 1 1/2 | 38 | 39 7/16 | 1003 | 26 1/4 | 667 | 20 1/2 | 521 | 5 | 127 | 43 | 20 |
| <input type="checkbox"/> O8631 | 31 | 1 1/2 | 38 | 57 7/16 | 1461 | 26 1/4 | 667 | 20 1/2 | 521 | 5 | 127 | 57 | 26 |
| <input type="checkbox"/> O8639 | 39 | 1 1/2 | 38 | 69 7/16 | 1765 | 26 1/4 | 667 | 20 1/2 | 521 | 5 | 127 | 66 | 30 |
| <input type="checkbox"/> O8678 ¹ | 78 | 1 1/2 | 38 | 69 7/16 | 1765 | 26 1/4 | 667 | 40 1/4 | 1022 | 5 | 127 | 116 | 53 |
| <input type="checkbox"/> O8639W ² | 39 | 1 1/2 | 38 | 69 7/16 | 1765 | 18 1/4 | 463 | 28 1/2 | 724 | 5 | 127 | 52 | 24 |

¹double width rack

²wide-opening rack; side-loaded trays



CONSTRUCTION... Heavy-duty, high tensile, all-welded extruded aluminum. Upper frame constructed of vertical uprights 1" x 2.5" x 1/8" thick extruded aluminum channels with top cross and side bracing of 1.25" x 1.25" x .070 wall extruded aluminum tubing, all fully welded together. Solid cap of .063 thick aluminum welded to uprights and cross bracing. Fully reinforced with welded-on horizontal 3/4" x 1" x .070 extruded aluminum stabilizing bars, one at each end.

CABINET MATERIAL... Heavy-duty, high tensile, extruded aluminum. Type 6463-T5 alloy.

BOTTOM FRAME... Constructed of 1/8" thick aluminum sheet with 4 sides bent down 1.375", with all corners welded smoothly. Tubular framework welded inside the 1/8" aluminum sheet for added rigidity.

ANGLE SLIDES... Compound guides are interlocking wall type, extruded aluminum panels. Each panel has a series of slides space on 1.5" centers, with 1/2" ledges and .090 wall thickness. Guides welded to vertical uprights.

CASTERS... Four 5" diameter platform type, all swivel with sealed ball bearing axle and non-marking tread. Caster plates welded to bottom of frame.

ACCESSORIES/OPTIONS...

- Caster locks (2)
- Corner bumpers (4)
- Perimeter bumper



Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com