



D R P R O O F E R L O



Proofer Cabinet, Roll-In, One-Cavity, (1) TLO Double or (2) Single Rack Capacity, Solid State Heat & Humidity Controls, Auto Water Entry, Full View Glass Door, Stainless Steel Interior and Exterior, Aluminum Floor, NSF, cETLus, ETL



PROJECT _____

ITEM NO. _____

NOTES _____

MODEL NUMBER: **DRIP1TLO**



*rack not included

FEATURES

- Even Airflow Heating System Maintains the Right Combination of Heat and Humidity for Optimal Proofing
- Proofs from Room Temperature up to 110°F (43°C)
- Relative Humidity up to 95%
- Automatic Water Fill System (no water pans required)
- Manual Controls
- Independent Controls for Heat, Humidity and Timer

CONSTRUCTION

- Stainless Steel Construction
- Aluminum Flush Floor Entry
- Ships in One Piece

CLEARANCES

Minimum Clearance from Combustible Materials:

- 4" (102mm) Sides & Back
- 24" (609mm) Top

OPTIONS & ACCESSORIES

- Stainless Steel Door (suffix SD)
- Door Bumpers (suffix DB)
- Prison Package (suffix PPE)
- Water Filter (PLF240) (recommended)

WARRANTY

- One Year Labor & Two Year Parts



Model	Crated Weight	Overall Dimensions				Single Rack Capacity	Double Rack Capacity	Door Opening	
		W	D	H	B			L	H
DRIP1TLO	500 (227)	38 1/2" (978)	56 1/2" (1435)	86" (2184)	52" (1321)	2	1	31 1/2" (826)	73 1/2" (1867)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

KCL & REVIT DRAWINGS UPON REQUEST

REVISION C | 5/18/23

Follow Us




Doyon

5600 13th Street, Menominee, MI 49858

906.863.4401 | 800.338.9886 | www.doyon.qc.ca



DRAWINGS


Model	Water Inlet	Electrical System			
		Volts	Phases	Amps	kW
DRIP1TLO	1/4"	120/208	1	35	7.2
	(6)	120/240		31	

