

Performance Data Sheet

Model: High Flow Series/HF05-MS

Use Replacement Cartridge HF05-MS

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42.



System tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of substances as listed below according to Standard 42.

Capacity: See chart on page 2

Contaminant Reduction Determined by NSF testing.

Substance Reduction	Average Influent	NSF/ANSI specified Challenge Concentration	Avg % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L ± 10%	96.8%	0.06 mg/L	N/A	≥ 50%	J-00089439

FOR COMMERCIAL USE ONLY

Application Guidelines/Water Supply Parameters	
Service Flow	See chart on page 2
Water Supply	Potable Water
Water Pressure	25 -125 psi (172 – 862 kPa)
Water Temperature	40° F - 100° F (4.4° C - 38° C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

Note: While the testing was performed under standard laboratory conditions, actual performance may vary.

Replacement Cartridge: HF05-MS. For estimated costs of replacement elements please call 866.990.9785 or visit our website at www.3Mpurification.com

WARNING

To reduce the risk associated with ingestion of contaminants:

- **Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system.**

CAUTION

To reduce the risk associated with property damage due to water leakage:

- **Read and follow** Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- **Do not** install if water pressure exceeds 125 psi (862 kPa). If your water pressure exceeds 80 psi, you **must** install a pressure limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.
- **Do not** install where water hammer conditions may occur. If water hammer conditions exist you **must** install a water hammer arrester. Contact a plumbing professional if you uncertain how to check for this condition.
- **Do not** install on hot water supply lines. The maximum operating water temperature of this filter system is 100° F (38° C).
- **Protect filter from freezing.** Drain filter when temperatures drop below 40°F (4.4°C).
- The disposable filter cartridge **must** be replaced every 6 months or at the specified service cycle, or sooner, if a noticeable pressure drop occurs.

Parts and service available from:



3M Purification Inc.
 400 Research Parkway
 Meriden, CT 06450, U.S.A.
 Tel 866.990.9785
 203.237.5541
 Fax 203.238.8701
www.3Mfoodservice.com
www.3Mpurification.com

3M is a trademark of 3M Company.
 © 2012 3M Company. All rights reserved.
 NSF is a trademark of NSF International
 INSTR4256 0912B

Performance Data Sheet

Model: High Flow Series

Use Replacement Cartridge HF05-MS

HF05-MS Cartridge Flow and Capacity Information

Head & Manifold	# of Cartridges	Flow Rate	Flush Instructions	Capacity
NH3-½ Series Head	1	.75 gpm (2.8 lpm)	Flush 1.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	1,500 gallons (5,678 liters)
VH3 Series Head	1	.75 gpm (2.8 lpm)	Flush 1.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	1,500 gallons (5,678 liters)
Twin Manifold Assembly, 2XX Series	2	1.5 gpm (5.7 lpm)	Flush 3.0 gallons through cartridge(s) before use (flush approximately 2 minutes)	3,000 gallons (11,356 liters)
Triple Manifold Assembly, 3XX Series	3	2.25 gpm (8.5 lpm)	Flush 4.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	4,500 gallons (17,034 liters)
DF Single Manifold Assembly, DF 1XX Series	1	.75 gpm (2.8 lpm)	Flush 1.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	1,500 gallons (5,678 liters)
DF Twin Manifold Assembly, DF2XX Series	2	1.5 gpm (5.7 lpm)	Flush 3.0 gallons through cartridge(s) before use (flush approximately 2 minutes)	3,000 gallons (11,356 liters)
DP Single Manifold Assembly, DP 1XX Series	1	.75 gpm (2.8 lpm)	Flush 1.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	1,500 gallons (5,678 liters)
DP Twin Manifold Assembly, DP2XX Series	2	1.5 gpm (5.7 lpm)	Flush 3.0 gallons through cartridge(s) before use (flush approximately 2 minutes)	3,000 gallons (11,356 liters)
DP Triple Manifold Assembly, DP3XX Series	3	2.25 gpm (8.5 lpm)	Flush 4.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	4,500 gallons (17,034 liters)
SF Single Manifold Assembly, SF 1XX Series	1	.75 gpm (2.8 lpm)	Flush 1.5 gallons through cartridge(s) before use (flush approximately 2 minutes)	1,500 gallons (5,678 liters)