CADDY Food Service Systems

page 2 of 2


Transfer and Storage Caddys for Racks and Trays



PROJECT:

ITEM NO:

LOCATION:





Dimensions					
Model	Length	Width	Height	Trays	
T-201-A	33"	21"	34 ³ / ₄ "	14" x 18"	
T-201-A-LB	33"	21"	24 ³ / ₄ "	14" x 18"	
T-201-B	37"	25"	34 ³ / ₄ "	16" x 22"	

General Specifications

Rack and/or Tray Caddy to be Caddy Corporation model T-


Frame to be of 1" O.D. 16 gauge stainless steel. Shelf to be 8" above the floor, of 18 gauge stainless steel with raised rounded edges on all sides, flanged down to form a 1-1/2" wide channel. Shelf corners shaped to fit contour of tubular frame and continuously welded to each leg at all contact points which eliminates unsanitary crevices. Casters to be 4" diameter heavy-duty swivel type with 3/4" stems and polyurethane tires.

Unit to be provided with the following accessories:

Accessories

	ACC-38 - Circular	bumpers.	(Add 4" to	length and v	width)
--	-------------------	----------	------------	--------------	--------

ACC-41 -	Caster brakes	on two diac	ional castors
 ALL-41 -	Casiei Diakes	OH IVVO CHAC	IOHAI CASIEIS





Dimensions					
Model	Length	Width	Height	Rack	
T-22	22 ¹ / ₄ "	22 ½"	8"	20" x 20"	

General Specifications

Rack and/or tray Caddy to be Caddy Corporation model T-22.

Frame to be 14 gauge stainless steel angles. Casters to be 4" diameter heavy-duty platform swivel type with polyurethane tires.

Unit to be provided with the following accessories:

Accessories

- ACC-50 Perimeter bumpers with replaceable corner bumpers. (Add 1-1/4" to length and width)
- ACC-52 Vertical corner bumpers only. Easy to replace. (Add 1-1/4" to length and width)



CADDY CORPORATION

509 Sharptown Road P.O. Box 345 Bridgeport, NJ 08014-0345

Tel: 856-467-4222 Fax: 856-467-5511