



701 S Ridge Avenue, Troy, OH 45374  
1-888-4HOBART • www.hobartcorp.com

## W32 AND W32C HAND-WRAP STATIONS



### W32 HAND-WRAP STATION

#### STANDARD FEATURES

- Easy to load film
- Low-temperature film cut-off system
- Stainless steel element
- 2-roll film capacity – 8" to 18" wide; top roll limited to 14" wide
- Fingertip film selection
- Maximum roll outside diameter 9½"
- 3" ID core plugs standard
- Rugged aluminum and stainless steel construction
- Adjustable height from 37" to 39½"
- Operates in all ambient temperatures
- Used with Hobart Semi-Automatic CLA Systems unless specified otherwise
- Compact 12½" deep x 25" wide design

#### MODEL

- W32-6 Hand-Wrap Station

#### SPECIFICATIONS

**CONSTRUCTION:** Rugged aluminum frame and roll core plugs with stainless steel wrapping surface and roll shafts plated steel.

**DIMENSIONS:** 12½ deep x 25" wide.

**FILM HOLDERS:** Two roll film selector.

**ELECTRICAL:** 100-120/60/1, input 1 amp.

**SHIPPING WEIGHT:** 50 lbs.



W32 AND W32C HAND-WRAP STATIONS

# W32 AND W32C HAND-WRAP STATIONS



701 S Ridge Avenue, Troy, OH 45374  
1-888-4HOBART • www.hobartcorp.com

## W32C HAND-WRAP STATION

### STANDARD FEATURES

- Easy to load film
- Low-temperature film cut-off system
- Stainless steel element
- 2-roll film capacity – 8" to 18" wide
- Fingertip film selection
- Maximum roll outside diameter 9½"
- 3" ID core plugs standard
- Rugged aluminum and stainless steel construction
- Adjustable height from 37" to 39½"
- Operates in all ambient temperatures
- Built-in hotplate
- Deep 26" x 22½" wide frame provides stability for freestanding use

### OPTIONS AT EXTRA COST

- 55A-SHELFA – Platter Shelf
- 69A-SHELF – Platter Shelf

### MODEL

- W32C-5 Hand-Wrap Station

### SPECIFICATIONS

**CONSTRUCTION:** Rugged aluminum frame and roll core plugs with stainless steel wrapping surface and roll shafts plated steel.

**DIMENSIONS:** **W32C** – 26" deep x 22½" wide.

**OPTIONAL PLATTERS:** **55A** – stainless steel platter shelf w/aluminum mounting brackets. 22" L x 14" W. 10 lbs. shipping weight. **69A** – stainless steel platter shelf w/aluminum mounting brackets. 14½" x 24½". 10 lbs. shipping weight.

**HOTPLATE ON W32C:** 8" x 15"

**FILM HOLDERS:** Two roll film selector. 9.5" capacity diameter x 18" maximum length.

**ELECTRICAL:** 100-120/60/1, input 11.3 amps, including hot plate and film cutting rod.

**SHIPPING WEIGHTS:** 60 lbs.; **55A** – 10 lbs.; **69A** – 5 lbs.



As continued product improvement is a policy of Hobart, specifications are subject to change without notice.