




NOTE: Faucet handles not included.

Project:_		AIA#
Item #:	Qty:	SIS#
Model #:		

Pipe Bridge Tower



Standard Features

- 1/4" stainless steel shanks with 3/16" restriction lines
- · All stainless steel faucets
- · Surface mount, stainless steel drain pans with removable, perforated inserts
- Tower mounting hardware for tops up to 4" thick
- Glycol cooled for recirculating system

Configurable Options

- 6, 8, 10, 12, 14 or 16 faucets
- · Grainline or mirror finish
- Rinser faucet centered on drain pan

Specifications

Materials

- Tower shell is 304 stainless steel; 0.065", 4" diameter
- Flange is 1/4", 304 stainless steel
- · 20 gauge stainless steel drain pan and perforated inserts

Shank Sizes

• 1/4" I.D. with 3/16" fitting

Drains

• 1/2" tailpiece on drain pan

Rinser Faucet (optional)

- · Accepts 3/8" cold water lead
- 30 psi water pressure regulator included
- 1.2 gallons per minute

Optional Rinser Faucet

Installation Notes

- Unit does not provide a 1" air gap
- Must be installed with external backflow prevention to meet applicable federal, state, and local plumbing code requirements.
- Install in-line water pressure regulator (included)
- A separate shut-off valve is recommended (not included)

NOTE: Rinser faucets are not intended for use with towers mounted to a refrigerator due to risk of water line freeze up.

03012383 Rinser Faucet Assembly



4004503 Conforms to NSF/ANSI STD 372

To view cleaning and care instructions, please visit: https://www.glastender.com/PDF/F-423-011 ss clean care.pdf

Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444


www.glastender.com

Specifications subject to change without notice. For current specifications please visit our website.

Approval/Notes:


Drawings


SIDE ELEVATIONS




PLAN VIEWS


NO RINSER FAUCET






WITH RINSER FAUCET







PIPE BRIDGE TOWER								
FAUCETS	6	8	10	12	14	16		
"A" WIDTH	45-1/4"	51-1/4"	57-1/4"	63-1/4"	69-1/4"	75-1/4"		
"B" WIDTH	11"	14"	17"	20"	23"	26"		
"C" WIDTH	28"	34"	40"	46"	52"	58"		