/// Frozen Drink Machine



115V – Gravity Feed Refrigerated Hopper Pre-Chills Mix

- ☆ Single Flavor // Countertop
- ightarrow Up to 165, 10oz drinks per hour
- ☆ 7.3 Qt Cylinder 16 Qt Hopper
- Higher capacity solution with greater flexibility to serve larger crowds alcoholic & non-alcoholic frozen beverage drinks



Patented high effciency heat exchanger allows fast freeze down with low energy consumption

Reduced Parts - Easy Cleaning

Reduced parts and single piece beater/shaft design improve cleaning time and operational experience.

Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

Low Mix Indicator & Freeze Protection

Light turns "ON" at low mix to alert operator to add mix. Prevents Freeze Ups when mix is out.

Refrigerated Hoppers, Standby, and Indicator

Maintains product temperature in mix hopper overnight and improves freeze and recovery time. Indicator lights for standby/night mode.

Safety Protections & Light Box Merchandising

High pressure switch prevents compressor overheating. Thermal overload protects motor and drive train. Illuminated flavor cards to attract more business

Self-closing Dispensing Valve

Automatically prevents product overflow after dispense

The Spaceman Difference

QUALITY

Affordable Quality

Designed by Aerospace Engineers

- Craft quality design, less investment
- Built to last
- Luxurious mouthfeel

VALUE Microcrystal Technology

3X Patented Freezing Speed

- ✓ Superior fast freeze
- Quick recovery
- Lowest energy cost per serving

<image>

SERVICE

Restriction-Free Service


Service on Your Terms

♦ No binding contracts

- ♦ No locked-in maintenance fees
- ♦ No monthly equipment costs



/// Frozen Drink Machine




Specifications

| Flavors | 1 |
|------------------------|-------------------|
| Freezing Cylinders | 1 x 6.9L / 7.3qt |
| Mix Hoppers | 1 x 15L / 15.85qt |
| Output Capacity (10oz) | 165 serves/hr |
| Max Serving Size | 32oz |
| Clearance Requirements | 152mm/6" |

| Weight | Kg/lb |
|----------|----------------------|
| Net | 108 / 240 |
| Shipping | 119 / 265 |
| Volume | 0.34 CBM / 12.12 CBF |

| Dimensions | Net (mm/in) | Shij | Shipping (mm/in) | |
|--------------|-------------|------------|------------------|--|
| Width | 384 / 15.1 | | 430 / 16.9 | |
| Depth | 687/ 27.0 | | 850 / 33.5 | |
| Height | 806 / 31.7 | 940 / 37.0 | | |
| Electrical | MFS | МСА | Power(kW) | |
| 110-120/60/1 | 20 | 15 | 1.3 | |
| | | | | |



Features

| Control System | One, Mechanical |
|-------------------------------|----------------------|
| Refrigerated Hopper | ~ |
| Hopper Agitator | ~ |
| Standby Mode | ~ |
| Auto Closing Dispensing Valve | ~ |
| Low Mix Indicator Light | ~ |
| Low Mix Indicator Alarm | ~ |
| Standby Mode | ~ |
| Standby Indicator Light | ~ |
| High Pressure Protection | ~ |
| Thermal Overload Protection | ~ |
| Indicator Lights | ~ |
| Low Mix Freeze Protection | |

Available Options

| Top Air Discharge Chute | ~ |
|-------------------------|----------|
| Spinner | ~ |