



Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Hand Sinks with Side Splashes, model _____.
 Constructed of all-welded type 304 stainless steel, with deep-drawn positive drain sink bowl, inverted "V" edge to prevent spillage, drain, splash-mounted faucet, and factory-installed side splash on both sides. Offered are the following hand sinks:

- Model #HSA-10-F-LRS.
- Model #HSAN-10-F-LRS. 12" side-to-side.
- Model #HSA-10-FDPE-LRS. Includes paper towel dispenser, soap dispenser, and electronic-eye sensor-beam faucet with 12-volt adaptor – 120/60/1.
- Model #HSA-10-FTWS-LRS. Includes tubular wall support.



HSA-10-F-LRS



HSAN-10-F-LRS



HSA-10-FDPE-LRS



HSA-10-FTWS-LRS

model #	includes	bowl size		overall size		weight	
		width in.	length x depth mm	width in.	length x height mm	lbs.	kg
HSA-10-F-LRS	faucet, basket drain and side splashes	9 ³ / ₄ "	13 ¹ / ₂ " x 343 x 173	14 ³ / ₄ "	18 ¹ / ₈ " x 376 x 480 x 324	14	6.4
HSAN-10-F-LRS	12" side-to-side, faucet, basket drain, side splashes	13 ¹ / ₂ "	9 ³ / ₄ " x 343 x 173	18" x 12" x 14 ¹ / ₄ "	457 x 305 x 362	17	7.7
HSA-10-FTWS-LRS	faucet, p-trap, tubular wall brackets, basket drain, side splashes	9 ³ / ₄ "	13 ¹ / ₂ " x 343 x 173	14 ³ / ₄ "	18 ¹ / ₈ " x 376 x 480 x 324	32	14.5
HSA-10-FDPE-LRS	electronic-eye faucet, towel/soap dispenser, basket drain, side splashes	9 ³ / ₄ "	13 ¹ / ₂ " x 343 x 173	14 ³ / ₄ "	19 ¹ / ₄ " x 28 ¹ / ₄ " x 376 x 489 x 718	33	15.0

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA
 Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065
www.eaglegrp.com
www.eaglegrpnews.com
www.eaglemhc.com

For custom configuration or fabrication needs, contact our SpecFAB® Division.
 Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.: _____
 Project No.: _____
 S.I.S. No.: _____

Hand Sinks with Side Splashes

MODELS:

- HSA-10-F-LRS
- HSAN-10-F-LRS
- HSA-10-FTWS-LRS
- HSA-10-FDPE-LRS

Hand Sinks

- Heavy gauge type 304 stainless steel all-welded construction.
- Inverted "V" edge rim retards spillage.
- Unique deep-drawn positive-drain bowl assures complete drainage to meet the most stringent health code requirements.
- Water inlet: 1/2" (13mm) NPS.
- Drain outlet: 1 1/2" (38mm) NPS.

Side Splashes

- Side splashes are factory-installed on both sides of sink.
- 16 gauge type 304 stainless steel.
- Tapered and rounded for safety.

Certifications / Approvals



Spec sheets available for viewing, printing or downloading from our online literature library at our websites