

BIM44GIFADA



32.38" x 14.5" x 23.5" (H x W x D)

ADA compliant built-in NSF-listed automatic defrost clear icemaker with integrated door frame to accept full overlay panels and an internal pump

Highlights:

32 3/8" height for use in ADA compliant settings

Flexible design allows built-in or freestanding use in 15" wide spaces

Integrated door frame accepts full overlay panels for a true custom look

Product Features:

ADA compliant	32 3/8" height fits under lower ADA compliant counters
Commercially approved	NSF listed for use in commercial establishments
Built-in pump	Internal pump allows more flexibility in placing the unit
Built-in capable	Make the best use of space by installing your appliance under the counter
Integrated door frame	Stainless steel door frame accepts full overlay panels to match adjacent cabinetry (panel size: 27 7/8" H x 14 5/8" W and at least 3/4" thick; maximum weight: 10 lbs.)
Clear ice cube production	Makes cubes sized at 3/4" x 3/4" x 1"
Automatic defrost	Reduced maintenance with auto defrost system
Insulated storage bin	Ice stays frozen longer inside this cold-protected bin
Fully finished black cabinet	Allows the unit to be used freestanding



BIM44GIFADA Specifications:

Overview	
Height of Cabinet	32.38" (82 cm)
Width	14.5" (37 cm)
Depth	23.5" (60 cm)
Defrost Type	Automatic
Door	Panel-Ready
Cabinet	Black
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	NSF
Amps	4.8
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	115.0 lbs. (52 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Ice maker	
Door Swing	LHD
Reversible	Factory Reversible
Drain Required	Yes
Daily Ice Production	50.0 lbs. (23 kg)
Ice Storage Capacity	25.0 lbs. (11 kg)
Ice Shape	Cube
Size of Cube	3/4" x 3/4" x 1"
Number of Ice Cube Sizes	1
Fan Type	Exterior
Refrigerant Type	R134a
Refrigerant Amount	3.88 oz.
High Side PSI	350.0
Low Side PSI	130.0
Interior Height	18.5" (47 cm)
Interior Width	12.0" (30 cm)
Interior Depth	16.0" (41 cm)
Level Legs	4

