



# EVERPURE® QUAD-XC<sup>2</sup> CARTRIDGE KIT

REPLACEMENT CARTRIDGE KIT FOR EVERPURE HIGH FLOW CSR PLUS-XC<sup>2</sup> SYSTEMS

Quad-XC<sup>2</sup> Replacement Cartridge Kit: EV9628-29



## APPLICATIONS

Foodservice

Use When Extreme Water Conditions  
Require Longer Life and Larger Capacity  
Carbon Filter

## FEATURES • BENEFITS

Reduces chlorine taste & odor and other offensive contaminants that can adversely affect the taste of beverages

Convenient replacement cartridge kit contains all necessary cartridges to service filters in specific High Flow CSR Plus combination systems

Exclusive precoat filtration provides superior chlorine taste & odor reduction and micro-filters dirt and particles as small as 0.5 micron in size by mechanical means

SS-IMF Cartridge inhibits limescale buildup in ice machines and coffee brewers

Kit includes one (1) Everpure EC210 prefilter, four XC<sup>2</sup> filter cartridges, and one SS-IMF with spacer

20" prefilter cartridge captures larger dirt particles and extends the life of the XC<sup>2</sup> cartridges

Proprietary Micro-Pure® II filtration media effectively inhibits the growth of bacteria on the filter media that can decrease product life

33% more capacity than MC<sup>2</sup> filter cartridge

NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means

## INSTALLATION TIPS

Install vertically with cartridge hanging down.

Allow 2-1/2" (6.35 cm) clearance below the cartridge for easy cartridge replacement.

Flush cartridges by running water through system for five (5) minutes at full flow.

Install SS-IMF Cartridge in SR-X bowl vertically with black O-band seal up.

## OPERATION TIPS

Change cartridges on a regular six (6) month preventative maintenance program.

Change cartridges when capacity is reached or when pressure falls below 10 psi (0.7 bar).

Change SS-10 Cartridge before Hydroblend™ compound is completely used up.

Replace Everpure EC210 Cartridge when dirt has penetrated through to the inner core of the cartridge.

Always flush the filter cartridges at time of installation and cartridge change.

## SIZING

Service Flow Rate: Maximum 6.7 gpm (25.4 Lpm)

# EVERPURE® QUAD-XC<sup>2</sup> CARTRIDGE KIT

## EV9628-29

### SPECIFICATIONS

#### Service Flow Rate

Maximum 6.7 gpm (25.4 Lpm)

#### Pressure Requirements

10 - 125 psi (0.7 - 8.6 bar), non-shock

#### Temperature

35 - 100°F (2 - 38°C)

#### Overall Dimensions

XC<sup>2</sup>: 29.69" L x 6.75" (75.4 cm x 17.1 cm)

EC210: 20" L x 3.38" D (50.8 cm x 8.5 cm)

SS-IMF\*: 6.875" L x 1.312" D  
(17.4 cm x 4.9 cm)

\*The SS-IMF Spacer (EV3114-69) may be used to extend the height of the SS-IMF cartridge by approximately 1-3/4" for a better fit into longer bowls.



System Tested and Certified by NSF International against NSF/ANSI Standards 42 and 53 for the reduction of:

#### STANDARD NO. 42 — AESTHETIC EFFECTS

Chemical Reduction  
Taste & Odor  
Chlorine

Mechanical Filtration  
Nominal Particulate, Class I

#### STANDARD NO. 53— HEALTH EFFECTS

Mechanical Filtration  
Cyst Reduction

EPA No. 002623-IL-002

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



### WATER QUALITY SYSTEMS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • FOODSERVICE.PENTAIR.COM  
800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC 3175, AUSTRALIA  
011.1300.576.190 TEL • 011.61.39.562.7237 FAX • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA  
86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301  
91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM  
+32.(0).14.283.500 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN  
81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA, SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01, KING'S CENTRE, SINGAPORE 169662  
65.6768.5800 TEL • 65.6737.5149 FAX • CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

### WARRANTY

Everpure water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.