

Project: \_\_\_\_\_ Location: \_\_\_\_\_ Item #: \_\_\_\_\_ Quantity: \_\_\_\_\_

### Standard Features

- Kettle System-Seamless deep-drawn 316 kettle liner with an integrally formed radius lip, 304 stainless draw off tube and welds, 304 stainless 2" compression draw-off
- 304 stainless kettle jacket
- Kettle protection system— thermostat temperature control, 150°F - 285°F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light
- Full body insulation between kettle jacket and outer casing
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded control console
- 304 stainless lift off cover on 20-30 gallon
- 304 stainless, one piece, domed cover, actuator-assisted on 40-125 gallon
- Perforated disc strainer, 1/4" holes
- Etched gallon markings
- Faucet bracket
- Adjustable bullet feet

### Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle\*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet\*
- Automatic water filling meter (ALAC-WS)
- Mixer/agitator, two speed (Call for pricing)
- Correctional Package\*
- Adjustable flanged feet\*

\* Call AccuTemp for additional information

### Electrical Options

208V, 240V, 380V, 415V, 440V, 480V

### Short Spec

AccuTemp Edge Series electric non-tilting kettle, 2/3 jacketed, model ALLEC-40. Seamless deep-drawn 316 kettle liner (up to 40 gallon, 304 40+ gallon) with integrally formed radius lip and 304 stainless steel kettle jacket. 2" compression draw-off valve that includes a perforated disc strainer (1/4" holes), pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light, field replaceable heating elements. 304 stainless domed cover with spring assisted (40-125 gallon units). Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 126°C). Etched gallon markings and faucet bracket. Adjustable bullet feet.

### Other Approvals



### Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Draw off drain hose (ALDIH)
- Disc strainer; solid or perforated, 1/8" or 1/4"\*
- Measuring strip (ALMS)
- Lift-off or two piece hinged\*
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)

\* Call AccuTemp for additional information



**ALLEC-40-QS**

Model ALLEC Electrical Specifications (Amperes per Leg)													
Gal	KW	208 Volt		240 Volt		380 Volt		415 Volt		440 Volt		480 Volt	
		1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø
40	15	72.1	41.6	62.5	36.1	39.5	22.8	36.1	20.9	34.1	19.7	31.3	18.0

MODEL ALLEC DIMENSIONS	
Gal	40
A	25.5
B	22.3
C	39.9
D	24.3
E	15.3
F	37.4
G	4.0
H	14.0
J(1)	75.0
J(2)	59.6
S	18.3
V	12.9
W	12.9

