

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle worktables, Budget series, model

Top to be constructed of heavy gauge type 430 stainless steel with 1% roll on front, 4% backsplash, and sides turned down 90°. Open front with 1% 0.D., stainless steel tubular crossbracing on sides and rear. Top reinforced with welded hat channels and sound deadened. Constructed with uni-lok® patented gusset system with the gussets recessed into the hat channels to reduce lateral movement. Legs to be 1% 0.D. stainless steel tubing, with stainless steel gussets and 1″ stainless steel adjustable bullet feet.



Patented uni-lok® System (Patent No. 5,165,349)	
worktable top sound-deadening tape between channel and top gusset recessed into channel reduces lateral movement "hat" channel frame 12-gauge gusset for 1%" leg is double-welded on backup plate and channel frame for added stability	-hat channel and table top are welded together

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com www.eaglegrpnews.com www.eaglemhc.com

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: quotes@eaglegrp.com

Item No.: _	
Project No.: _	
S.I.S. No.: _	
1	

Worktables with Backsplash and Stainless Steel Tubular Base —Budget Series

MODELS	
--------	--

☐ T2424STB-BS	□ <i>T24108STB-BS</i>	□T3072STB-BS	☐ T3660STB-BS
☐ T2430STB-BS	☐ T24120STB-BS	□T3084STB-BS	☐ <i>T3672STB-BS</i>
☐ T2436STB-BS	☐ T24132STB-BS	□T3096STB-BS	☐ T3684STB-BS
☐ T2448STB-BS	☐ T24144STB-BS	□ <i>T30108STB-BS</i>	☐ T3696STB-BS
☐ T2460STB-BS	☐ T3030STB-BS	□ <i>T30120STB-BS</i>	☐ <i>T36108STB-BS</i>
☐ T2472STB-BS	☐ T3036STB-BS	□ <i>T30132STB-BS</i>	☐ <i>T36120STB-BS</i>
☐ T2484STB-BS	☐ T3048STB-BS	□T30144STB-BS	☐ <i>T36132STB-BS</i>
☐ T2496STB-BS	☐ T3060STB-BS	□1 <i>T3648STB-BS</i>	☐ T36144STB-BS

Tabletop

- Patented uni-lok® gusset system (patent #5,165,349): gussets are recessed into hat channel, reducing lateral movement.
- Top reinforced with welded-on hat channel.
- Sound-deadened between top and channels.
- 4½" (114mm)-high 90° backsplash with 1" (25mm) turn at 90°.
- 1½" (38mm)-diameter 180° rolled edge on front. Ends are turned down 90°, providing for flush installations when required.
- · Heavy gauge type 430 polished stainless steel.

Crossbracing—1¼" (38mm)-diameter

- Heavy gauge stainless steel.
- Aluminum castings join crossbraces, legs and rear brace.

Legs—1%" (41mm)-diameter

- Tables 96" (2438mm) and longer come with six legs or more.
- Heavy gauge stainless steel.
- 1" (25mm) adjustable stainless steel feet.

Options / Accessories

Drawer	Duplex receptacles
■ Lock	Overshelves
□ Casters	Pot rack
Power strip (for material handling)	☐ Sink
Knockdown Welded Base	☐ Stabilizer Bar (for 30
(see back page)	and 36"-wide tables)

Certifications / Approvals









EG10.47A Rev. 07/23




Item No.:	
Project No.:	
S.I.S. No.:	

Worktables with Backsplash and Stainless Steel Tubular Base—Budget Series







	# of	width		length		weight	
model #	legs	in.	mm	in.	mm	lbs.	kg
T2424STB-BS	4	24″	610	24"	610	41	18.6
T2430STB-BS	4	24″	610	30″	762	46	20.9
T2436STB-BS	4	24"	610	36″	914	51	23.1
T2448STB-BS	4	24″	610	48″	1219	61	27.7
T2460STB-BS	4	24″	610	60″	1524	71	32.2
T2472STB-BS	4	24″	610	72″	1829	81	36.7
T2484STB-BS	4	24″	610	84"	2134	91	41.3
T2496STB-BS	6	24″	610	96″	2438	101	45.8
T24108STB-BS	6	24"	610	108″	2743	111	50.3
T24120STB-BS	6	24"	610	120″	3048	121	54.9
T24132STB-BS	8	24"	610	132″	3353	131	59.4
T24144STB-BS	8	24″	610	144″	3658	141	64.0
T3030STB-BS	4	30″	762	30″	762	51	23.1
T3036STB-BS	4	30″	762	36″	914	56	25.4
T3048STB-BS	4	30″	762	48″	1219	66	29.9
T3060STB-BS	4	30″	762	60″	1524	76	34.5
T3072STB-BS	4	30″	762	72″	1829	86	39.0
T3084STB-BS	4	30″	762	84″	2134	96	43.6
T3096STB-BS	6	30″	762	96″	2438	106	48.1
T30108STB-BS	6	30″	762	108″	2743	116	52.6
T30120STB-BS	6	30″	762	120″	3048	126	57.2
T30132STB-BS	8	30″	762	132″	3353	136	61.7
T30144STB-BS	8	30″	762	144″	3658	146	66.2
T3648STB-BS	4	36″	914	48″	1219	71	32.2
T3660STB-BS	4	36″	914	60″	1524	81	36.7
T3672STB-BS	4	36″	914	72″	1829	91	41.3
T3684STB-BS	4	36″	914	84″	2134	101	45.8
T3696STB-BS	6	36″	914	96″	2438	111	50.3
T36108STB-BS	6	36″	914	108″	2743	121	54.9
T36120STB-BS	6	36″	914	120″	3048	131	59.4
T36132STB-BS	8	36″	914	132″	3353	141	64.0
T36144STB-BS	8	36″	914	144″	3658	151	68.5

NEW Option for Worktables with Stainless Steel Base: Knockdown Welded Base



- · Precision machined stainless steel threaded inserts pressed into 16 gauge 1%"-diameter leg sections for knockdown construction
- · C-Frame stainless steel tubular base

Add suffix "-KDWB" to worktable model number (ex: T2436STB-BS-KDWB). See EG8217 for more info.

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065 www.eaglegrp.com • www.eaglegrpnews.com • www.eaglemhc.com

Printed in U.S.A. ©2023 by Eagle Group

Rev. 07/23