

# DESIGNER LINE ROLL-THRU WARMER

**Model: DL2WI-RT-E**



## 2-Section Extra-High Roll-Thru Warmer with 72" Cart Capacity

DL2WI-RT-E - Stainless steel front, aluminum end panels and interior  
 DL2WI-SA-RT-E - Stainless steel exterior, aluminum interior  
 DL2WI-SS-RT-E - Stainless steel exterior and interior



### Options and Accessories

(upcharge and lead times may apply)

Chrome or stainless steel shelves	<b>Correctional Facility Options</b>
Rehinging of door (consult factory)	<ul style="list-style-type: none"> <li>One way security screws</li> </ul>
Custom laminates	<ul style="list-style-type: none"> <li>Locking hasp (lock not included)</li> </ul>
Half doors	<ul style="list-style-type: none"> <li>Stainless steel mesh cover</li> </ul>
Special electrical req. (consult factory)	<ul style="list-style-type: none"> <li>Coverless hinges</li> </ul>

Consult factory for other model configurations, options and accessories.



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

### Standard Model Features

#### HEATING SYSTEM

Self contained, performance rated "plug" heating system  
 90°F to 180°F temperature range  
 Unique air flow distribution ducts

#### CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation  
 Smooth, polished chrome workflow door handles  
 Cam action, lift off hinges  
 Magnetic snap in Santoprene™ door gaskets  
 Cylinder lock in each door  
 Self-closing doors  
 72 1/2" high door opening (72"H rack capacity\*)

#### MODEL FEATURES

Electronic controller with digital display & hi-low alarm  
 Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site  
 Removable stainless steel rack guides  
 Removable stainless steel ramps  
 Reinforced stainless steel floor

\* Racks not supplied

APPROVAL:

# Model Specifications

## DIMENSIONAL DATA

Net Capacity (cubic feet)	68 (1926 cu l)
Width, Overall (inches)	68 1/2 (1740 mm)
Depth, Overall (inches) (including handles)	38 3/4 (984 mm)
Depth (inches) (less doors)	32 (813 mm)
Depth (inches) (doors open 90°)	98 (2489 mm)
Clear Door Width (inches)	27 3/8 (695 mm)
Clear Door Height (inches)	72 1/2 (1842 mm)
Height, Overall (inches)	92 (2337 mm)
Number of Doors	4
Rack Capacity** (per section)	2

## ELECTRICAL DATA



Voltage	208-230/60/1
Feed Wires (including ground)	3
Total Amps (International)	13.9 (13.9)
Total Wattage @ 208-230 volts	3000
10 ft. Cord/Plug (International)	No (No)

## SHIPPING DATA

Height - Crated (inches)	97 (2464 mm)
Width - Crated (inches)	77 (1956 mm)
Depth - Crated (inches)	42 (1067 mm)
Volume - Crated (cubic feet)	176 (4984 cu l)
Weight Std - Crated (pounds)	720 (327 kg)
Weight SS - Crated (pounds)	820 (372 kg)

\*\* Maximum rack size including wheels - 27"W x 29"D x 72"H  
 Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

# Model Plan Views



**IMPORTANT NOTE:** If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides.

**Continental**  
 Refrigerator

Toll-Free: 800-523-7138  
 Phone: 215-244-1400  
 Fax: 215-244-9579

539 Dunksferry Road  
 Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



PROUDLY  
 DESIGNED & ASSEMBLED  
 IN THE U.S.A.

Intertek

© Copyright 2021. Continental Refrigerator.  
 A Division of National Refrigeration & Air Conditioning Products, Inc.

REVISED: 7/19/24