

Pocket Test Thermometers (2" dial)



The 2" glass lens series feature a stainless steel vessel clip, allowing for multiple uses. Made with the same quality we put into our 1" dial pocket test, except these units can be seen from further away. Ideal for reading temperatures in overhead ductwork or piping as well as any cooking application where a larger dial is desirable when reading the temperatures.

MODELS: 2236-02, 2236-06, 2236-14, 2236-28, 2236-29, 2238-02, 2238-06, 2238-12, 2238-14, 2238-15, 2238-24

Specifications: 2236-02, 2238-02

Instrument Range	-40° to 180°F/-40° to 80°C
Accuracy	±2°F
Weight	2236-02 - 1.4 oz 2238-02 - 2.5 oz

Specifications: 2236-06, 2238-06

Instrument Range	0° to 220°F/-10° to 100°C
Accuracy	2236-06 - ±4°F 2238-06 - ±2°F
Weight	2236-06 - 1.4 oz 2238-06 - 2.5 oz
Other	2236-06 - Red protective sheath with clip 2238-06 - Stainless steel vessel clip

Specifications: 2236-14, 2238-14

Instrument Range	50° to 550°F/25° to 275°C
Accuracy	±5°F
Weight	2236-15 - 1.4 oz 2238-14 - 2.5 oz
Other	Stainless steel vessel clip

Specifications: 2236-28

Instrument Range	20° to 80°F
Accuracy	±2°F
Weight	1.5 oz ⁹

Specifications: 2236-29, 2238-24

Instrument Range	130° to 210°F/54° to 99°C
Accuracy	±2°F
Weight	2236-29 - 1.5 oz 2238-24 - 2.5 oz

Specifications: 2238-12

Instrument Range	35° to 180°F
Accuracy	±2°F
Weight	1.25 oz
Other	Stainless steel vessel clip


Specifications: 2238-15

Instrument Range	25° to 125°F
Accuracy	±2°F
Weight	2.5 oz
Other	Stainless steel vessel clip


Mechanical Pocket Test Thermometers

Features

- 2" models - glass or polystyrene lens
- Recalibrateable
- Stainless steel stem
- Bimetal coil movement
- 2236 series 5" stem length
- 2238 series 8" stem length




Model 2236-14




Model 2236-02




Model 2236-29




Model 2238-06



Model 2238-12



Model 2238-14



Model 2238-24