

Project: _____ Location: _____ Item #: _____ Quantity: _____

Standard Features

- Kettle System-Seamless deep-drawn 316 kettle liner (up to 40 gal, 304 liner for 40+ gallon) with an integrally formed radius lip, 304 stainless draw off tube and welds, 304 stainless 2" compression draw-off
- 304 stainless kettle jacket
- Kettle protection system— thermostat temperature control, 150°F - 260°F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, safety pilot control
- Full body insulation between kettle jacket and outer casing
- Electric ignition, 120V standard
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded control console
- 304 stainless, one piece, domed cover, actuator-assisted on 40-125 gallon
- Perforated disc strainer, 1/4" holes
- Adjustable bullet feet
- Etched gallon markings
- Faucet bracket

Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet*
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALAC-WS)
- Mixer/agitator, two speed (Call for pricing)
- Correctional Package*
- Adjustable flanged feet (ALFF-200)
- 316 Liner for 40+ Gallon (AL316LNR)

* Call AccuTemp for additional information

Electrical Options

120V, 208V, 240V

Short Spec

AccuTemp Edges Series gas powered, 2/3 jacketed, non-tilting floor kettle, model ALLGB-40. Seamless deep-drawn 316 kettle liner with integrally formed radius lip and 304 stainless steel kettle jacket. 2" compression draw-off valve that includes a perforated disc strainer (1/4" holes), pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light. 304 stainless domed cover with spring assisted. Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 126°C). Etched gallon markings and faucet bracket. Adjustable bullet feet.

Other Approvals

GAS-FIRED



Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Gas quick disconnect 1/2"*
- Flexible gas hose 3/4" x 60" (ALTQDH)
- Draw off drain hose (ALDIH)
- Disc strainer; solid or perforated, 1/8" or 1/4"*
- Measuring strip (ALMS)
- Lift-off or two piece hinged*
- One piece actuator-assisted lid, 20-60 gal. (ALACT-M)
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)

* Call AccuTemp for additional information



ALLGB-40-QS

**INSULATED SELF-CONTAINED KETTLE-
ALLGB-40-QS**

40 GALLON CAPACITY—Gas, 2/3 Jacketed Insulated
for Safety™ Deep Drawn Construction Non-
Tilting, Floor Mounted. Made in USA

GAL	BTU Rating	
40	79,900	
Supply Piping: 1/2" IPS		120 volt (standard)
Supply Piping: 3/4" IPS		208/240 volt (optional)
Supply Pressure: 5-7" W.C. (nominal)		50/60 Hz
		1 Phase
		1 Amp
Outlet Pressure Factory Setting: 3.5" W.C.		

MODEL ALLGB DIMENSIONS										
Gal.	A	B	C	D	E	F	J	S	V	W
40	25.5	22.3	42.0	25.8	14.6	37.1	77.5	18.9	10.3	17.4

