

Product Specifications

74 cu ft Freezers, Reach-In

- Improve the flow and function of your space by having frozen items where you need them most
- Comfortably fits 18" x 26" sheet pans (not included)
- Glass & solid door options
- 8 casters included (2 locking) for easy mobility
- LED lighting on glass door models





UCFZ585-SS71A

UCFZ585-SG71A


Model	Description	Voltage/Hz/Amps	Shipping Weight
UCFZ585-SS71A	Freezer, Reach-In, Solid Door	115v / 60hz / 20	650 lb
UCFZ585-SG71A	Freezer, Reach-In, Glass Door	115v / 60hz / 20	750 lb

Specifications
UCFZ585 dimensions: 83 ¹⁵ / ₃₂ " H x 85 ³ / ₆₄ " W x 31 ¹⁵ / ₃₂ " D
AISI 304 stainless steel interior and exterior with locks
Autodefrost
CFC-free high-density polyurethane insulated cabinet
Electronic digital temperature control with alarms
Environmentally friendly R290 refrigerant: 2 x 3.5 oz (2 x 0.100kg)
Factory pre-wired for dedicated outlet, 11 ft. cord and plug included NEMA 5-20P
High efficiency compressor
High efficiency evaporator coil & condenser
NSF/ANSI Standard 7 compliant
Removable magnetic gasket for easy cleaning
Self-lubricating, sealed cast iron evaporator fan motor with high volume air flow design
Temperature range: -13°F to 14°F
Volume of 74 cu ft
3 sections, includes 9 epoxy coated wire shelves

Accessories	Description	Shipping Weight
ULA4080584	(1) Stainless steel shelf guide for all reach-ins except UCRE553 & UCFZ553, 24 ³ /4"	.88 lb
ULAQ32-0002	(1) Epoxy coated wire shelf, 20 1/8" x 25 5/8" for reach-ins	7 lb
ULA80110300	Interior LED lighting kit for solid door reach-ins	2.2 lb



Front (Closed - Solid Door)





Front (Open) 1 ³⁷/₆₄" (40 mm) 2 ¾₆₄" (60 mm) ۲ ۲ 40 PIL NAME 11 242 2 ¾4″ 4 ²³/₃₂" (120 mm) 4 ²³/₃₂″ (120 mm) (60 mm) 77 ^{9/16}" (1970 mm) 23 5⁄8″ (600 mm) 23 ⁵⁄8″ (600 mm) 23 5⁄8″ (600 mm) 2 3/64" (60 mm) þ П

Тор

85 ³/₆₄" (2160 mm)

Front (Closed - Glass Door)





Commercial Warranty

Ħ

4

27 61/64"

(710 mm)

卜

Π

3 Year (parts & labor) / 5 year sealed system (parts) See complete warranty for details

卜

Π

녝

H

5 ²⁹/₃₂" (150 mm)

Π

