

#### PROJECT: \_\_\_\_ ITEM # \_ \_\_ QTY: MODEL # AIA # \_\_\_\_ \_\_\_\_\_\_ SIS # \_

# **CHEF BASE FREEZER**

# CBF52HC

## **EXCLUSIVE WARRANTY**

- 7 Year Parts, Labor and Compressor
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)







### CABINET CONSTRUCTION

- Stainless Steel Exterior (galvanized back & bottom)
- Aluminum Interior
- Marine Top Standard
- 3" Heavy Duty Casters
- 10' Cord And Plug (see electrical data for details)

#### REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All Environmental Concerns
- Adaptive Defrost For Reduced Energy Consumption And More **Consistent Product Temperatures**
- Electric Defrost Heater With Hot Gas Condensate Evaporation
- Freezer Capable Of Maintaining Product Temperature Of -10°F

#### **FEATURES**

- High Performance Refrigeration System With Electronic Control
- Top Weight Capacity 1000 lbs
- Heavy-Duty Drawer Slide Roller System
- 275 lbs Drawer Load Rating (per drawer)
- Heavy Duty, Fire-Proof Insulated, 16 Gauge Top
- No Heat Shield Required (must adhere to proper clearance per owners manual)
- Accommodates 6" Deep Full Size Food Service Pans (not included)
- Self-Closing Drawer Feature
- One Piece, Snap-In, Magnetic Drawer Gasket
- Compressor Available On Left Or Right, Specify At Time Of Unit Order



#### **OPTIONS & ACCESSORIES**

- · Additional Pan Supports
- Stainless Steel Back · Stainless Steel Interior

Drawer Locks

- 6" Casters
- 6" Legs Or 6" Seismic Legs
- Flat Top Overhang (any size up to 6" overhang on each side)
- Remote Models\* (6" legs only) (refrigerant must be specified at time of order, see note on back page)


#### 3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168 Sales@VictoryRefrigeration.com VictoryRefrigeration.com


Rev. 9/1/24 Printed in U.S.A.


APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_












#### **Drawer Configurations**



We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

3 3/16'	' Bottom &	1″	Rear	clearance	is	required
---------	------------	----	------	-----------	----	----------

CHARACTERISTICS		ELECTRICAL DATA	SHIPPING DETAILS			
Net Capacity (cubic ft.)	8.06	Cabinet Voltage	115/60/1	Height	27″	
Width, Overall (in.)	52″	Total Amperes	5.0	Width	58″	
Depth, Overall (with handle)	34 1/4"	NEMA Plug (10' cord)	5-15P	Depth	38"	
Height Overall (with casters)	eight Overall (with casters) 24 3/8" REFRIGERATION DATA				400 lbs	
Depth, Drawer Open 90°	57 1/4″	Condensing Unit Size, HP	1/2			
Drawer Openings (in.)	27 3/8" X 6 1/2"	Refrigerant*	R-290	*NOTE: Remote units are field		
No. Of Drawers / Pans (full size)	2/4	Capacity (BTU/HR) (100°F/-20°F)	1725	wired and come with 6" legs. Refrigerant must be specified at		
		Heat Rejection (BTU/HR)	2588	time of order.		
		Charge (lbs/grams/ounces)	0.287 / 130 / 4.59			

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com Rev. 9/1/24 Printed in U.S.A.

