

Item #:_____ Date:__

Qty:_____ Approved By:___

Royal Series

Electronic Sensor Faucet Single Hole Deck Mount



DESCRIPTION

Battery Powered Electronic Sensor Faucet with Control Module, 4" Deck Plate, Spout Supply Hose & Mounting Hardware, Polished Chrome Finish, Cast Spout

STANDARD FEATURES

- Single Hole Deck Mount
- Infrared Sensor Operated
- Battery Powered Control Module, (4) AA Batteries Included
- Built-In Filter to Prevent Debris from Entering Solenoid Valve
- Low Battery Indicator Light
- Battery Life 1-3 Years Based on Usage
- Warranty: 3 Years

OUTLETS

Standard Aerator	Suffix
0.50 GPM Aerator	A1
1.00 GPM Aerator	A2
1.50 GPM Aerator	A3
2.20 GPM Aerator	A4

Lan	Suffix	
	0.50 GPM Outlet	B1
	1.00 GPM Outlet	B2

Multi-Laminar Flow Outlet	Suffix
0.35 GPM Outlet	K2
0.50 GPM Outlet	K3
1.00 GPM Outlet	K4

Van	dal Resistant Aerator	Suffix
	0.50 GPM Aerator	C1
	1.00 GPM Aerator	C2
	1.50 GPM Aerator	C3

Vandal Resistant Laminar Flow Outlet	Suffix
0.50 GPM Outlet	D1
1.00 GPM Outlet	D2
1.50 GPM Outlet	D3

Vandal Resistant Multi-Laminar Flow Outlet	Suffix	
0.35 GPM Outlet	L1	
0.50 GPM Outlet	L2	

SPECIFICATION	S
Water Inlet	Preinstalled M10*1.0 Spout Supply Hose
Control Module Inlet (Mixing Valve)	1/2 Female NPS
Temp. Range	40°F - 180°F
Water Pressure	20-120 psi
Sensor Type	Infrared
Default Time Out	30 Seconds
Default Shut-Off Delay	1 Second
Default Auto Flush	Off
Sensor Range	3/4" - 8-1/4"
Battery Life	500,000 cycles
Material	Solid Brass
Finish	Polished Chrome
Weight	5 lbs.

PRODUCT COMPLIANCE

- ASME A112.18.1-2011/CSA B125.1-11
- NSF-61
- NSF/ANSI 372
- Meets ANSI A117.1 (ADA)
- CEC Listed
- Massachusetts Approved

WARNING: Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes. California Proposition 65 Warning

NSF




16-654P-Model:

Item #:_____ Date:__

Qty:_____ Approved By:___

Electronic Sensor Faucet Single Hole Deck Mount



Replacement Parts				
	Model	Description		
1	16-506	Convex Sensor with Cable		
2	16-517	Spout Supply Hose		
3	16-198	Control Module		
4	16-189	4" Deck Plate		

Spout Supply Hose


- 1/2" NPS Female x M10*1.0 Male Thread
- 30"L

Control Module

- 5-3/8"W x 3-1/4"H x 2 1/8"D
- Battery powered (4) AA or AC powered (AC adapter not included)

Flow Control	Setting								
Shut-Off Delay	1s			10s			15s		
Auto Flush	ON					0	FF		
Auto Time Out	15s	20s	25s	30s	45s	1m	2m	10m	

Default Flow Control Setting Highlighted in Gray



Krowne Metal Corporation • 100 Haul Rd. Wayne, NJ 07470 • P: (800) 631-0442 • customerservice@krowne.com • krowne.com Rev. 01/2021 • No. 16-654P-__ Due to our commitment to continued product improvement, specifications are subject to change without notice.

Royal Series