

SMART•THERM®

Experience the trusted quality and reliability you've come to expect from Dinex with the Smart•Therm® Induction Charger.

Features & Benefits

- Base holds the food temperature up to 60 minutes
- User Friendly - Simple to understand; charges in 16-20 seconds; automatic base detection
- Smart Boosting – Automatically senses base charge level and applies additional charge to quickly bring base up to optimum temperature
- Attractive, tough, and easy-to-clean tempered glass surface is impact and heat resistant
- Watertight - Zero exposed electrical components
- Keep Warm Feature - When the base is left on the charger it will give a small charge every 30 seconds to maintain temperature for up to 2 hours before the charger goes into sleep mode
- Safe - Base remains cool to the touch, even after charging

Built-in RFID tag relays information to the charger to get consistent and accurate temperatures every time—protects the base from over-heating



Internal phase changing material requires lower energy input to hold temperatures longer

Smallest, most compact induction unit in the industry



Charge up to 3 bases per minute on (208V or 240V) – 1-Phase outlet

Completely sealed, watertight design with zero exposed electrical components

LCD display tracks charging progress

Charges DX8210 bases in 16-20 seconds with up to a 60-minute hold time



SKU	Description	Color Variations	Pack
DX8210 Δ	Base for Smart•Therm® Induction Charger	03, 31, 44, 50, 61, 84	12 ea

Δ More than one color option available

SKU	Description	Electrical	L x D x H	Pack
DX811220	Smart•Therm® Induction Charger	(208V/240V) 1-Phase	Inches (13.66" x 18.5" x 5.41") / cm (34.7 x 47 x 13.74 cm)	1 ea