



# SMARTSTEAM PRO

## BOILERLESS STEAMER ELECTRIC MODEL (2)GSSP-BL-5ES

Double-stacked, stand mounted, stainless steel, boilerless convection steamer. Each steamer cavity with a self-contained atmospheric 12 KW electric steam generating 2.5-gallon reservoir.

|               |  |
|---------------|--|
| PROJECT NAME: |  |
| LOCATION:     |  |
| ITEM NO:      |  |
| QTY:          |  |
| MODEL NO:     |  |
| AIA NO:       |  |
| SIS NO:       |  |
| CSI SECTION:  |  |

**SHORT FORM SPEC:** Shall be a Groen SmartSteam Pro model (2)GSSP-BL-5ES, two stacked single compartment boilerless electric convection steamer (\_\_\_\_\_volt, \_\_\_\_\_phase). Rear-panel vents. Fully assembled from factory on stainless steel stand. Water-resistant touchscreen control with self-diagnostics and programmable features. Capacity to be (5) 12"x20"x2-1/2" hotel pans per cavity. Dual water connection per cavity, auto fill and drain, mirrored interior, side-mounted convection fan. 2.5-gallon water reservoir protected by removable steam lid for easy cleaning and increased steam recovery. Slammable, field-reversible, hands-free stainless steel door latch. Standard 1-year parts and labor warranty with additional 1-year warranty upon completion of scheduled free Groen startup. 5-year cavity warranty. Made in the U.S.A.

**CONSTRUCTION:**

- Stainless steel construction with removable non-louvered side panels
- Rear-panel vents for decreased water/spray ingress
- Stainless steel field-reversible door with continuous hinge and single-piece replaceable seal
- Hands-free door latch provides positive closure when pushed or slammed shut
- Hidden door switch cuts power to blower fan and steam generating reservoir when door is opened
- Pan support racks are stainless steel and easily removed for cleaning
- Removable stainless steel condensate tray located under cavity door
- 5-year cavity warranty
- ASA component control (fan, valve, etc.) allows visibility of component operation on screen
- USB port for service use and firmware updates
- 5-day storage of error code history

**FINISH:** Cabinet exterior and door feature a #3 uniform finish. Cavity interior is polished stainless steel with mirrored finish.

**UL & CUL LISTING:** Steamer is UL and cUL listed.

**SANITATION:** NSF Listed. Designed and manufactured to meet all known health codes.

**CONTROLS:**

- Water resistant, user-friendly touch screen
- Self diagnostics
- User selected or automatic holding feature after timed cook completes
- 10 nameable pan timers
- Door open alert
- Clock
- Programmable delime schedule with simple on-screen walk-through and notifications
- "+1 minute" button quickly adds to cook time
- User optional load compensating timer

**PERFORMANCE FEATURES:**

- Powerful, side-mounted blower increases steam velocity for efficient distribution throughout cavity and between loaded pans
- 2.4 KW of electric power input per 2-1/2" deep steam pan
- Removable steam lid increases recovery times and aids in ease of cleaning
- Typical heat up is zero to ready in 15 minutes or less
- Cavity maintains warmth and ready status for instant steam between loads

**ATMOSPHERIC STEAM RESERVOIR:**

- High-efficiency electric-heated steam generating reservoir provides atmospheric steam to the cavity at a temperature of approximately 212°F
- Built-in water sensing system
- Electric heating elements are not immersed in water and are replaceable from the rear

**PAN CAPACITY:**

| Pan Size/Type    | Per Cavity | Total |
|------------------|------------|-------|
| 12 x 20 x 1"     | 10         | 20    |
| 12 x 20 x 2-1/2" | 5          | 10    |
| 12 x 20 x 4"     | 3          | 6     |

**INSTALLATION:** Steamer requires 208, 240, or 480 Volt, 3-phase electrical service. Each cavity has (2) 3/4" NH cold water supply line connections. The steamer has a single 2-1/2" free venting drain connection. All units ship three-phase, and are field convertible to single-phase operation.

CONTINUED ON BACK...

**OPTIONS/ACCESSORIES:**

- Prison Package (per cavity)
- Field Drain Tempering Kit
- Flanged Foot Kit for Stand
- Caster Kit for Stand
- Heat Shield Kit (field installed)
- Water Treatment Systems
- Water Treatment Replacement Cartridges
- 1-Year Warranty Extension

**ADDITIONAL RESOURCES:**

[Request A Quote](#)

[Sales Tools](#)

[Find A Rep](#)

**WATER QUALITY REQUIREMENTS:**

- Containment
- Water Supply
- pH
- 7 to 9
- Total Dissolved Solids (TDS)
- 30 to 60 ppm
- Hardness
- less than 60 ppm
- Chlorine and Chloramine
- less than .1 ppm
- Chlorides
- less than 30 ppm
- Silica
- less than 12 ppm
- Undissolved Solids
- less than 5 microns

In order to accurately choose the correct water treatment solution, a water quality test has to be performed. If a "Free Start-up" is requested, the ASA will perform a water quality test and Unified Brands will be able to suggest the best solution for your water quality. If a "Free Start-Up" was not requested prior to installation, then your local manufacturing representative can coordinate this for you.

After the "Free Start-up" is performed, Unified Brands will add an additional 1-year parts and labor warranty. If Unified Brands suggests a water treatment system, the system is purchased from Unified Brands, installed and maintained, water related service issues will be covered for the duration of the warranty period.

**ORIGIN OF MANUFACTURE:**

Designed and manufactured in the United States.

