




# POWER PACK - AIR COOLED

PREMIUM - 1 PUMP - 2,300 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.



**MMPP4301**



5-15P



Part No.	Description	Shipping Weight
<input type="checkbox"/> MMPP4301	Air cooled power pack, 1 pump and motor	55 kg 120 lbs

## Operating Performance

<b>Compressor</b>	1/3 HP	<b>Charge</b>	0.34 kg (12 oz)
<b>BTU per hour</b>	2,300	<b>Refrigerant Running Pressure</b>	18 (low) 140 (high)
<b>Plug Type (NEMA #)</b>	5-15P	<b>Bath Capacity</b>	43.5 litre (11.5 gallons)
<b>Voltage</b>	115	<b>Pump Type</b>	Rotary Vane
<b>Running</b>	12.1A	<b>Push In Connector</b>	12.7mm (1/2") O.D.
<b>Refrigerant</b>	R-134a		

## Dimensions

