

DT2x

Direct Thermal Label Printer

Ultra-light and compact, the DT2x direct thermal printer works seamlessly with the versatile S2000 Jr Price Computing Scale.



CAS

www.cas-usa.com

DT2x | Direct Thermal Label Printer

SPECIFICATIONS

MODEL		DT2x
Print Method		Direct Thermal
Resolution		203 dpi (8 dots/mm)
Print Speed		7 IPS (177 mm/s)**
Print Width		2.12" (54 mm)
Print Length		Min 0.16" (4 mm)** / Max 68" (1727 mm)
Processor		32 Bit RISC CPU
Memory	Flash	4 MB Flash (2 MB for user storage)
	SDRAM	16 MB
Sensor Type		Fixed transmissive sensor, central aligned, adjustable reflective sensor
Media	Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
	Width	Min 0.6" (15 mm) ~ Max 2.36" (60 mm)
	Thickness	Min 0.0024" (0.06 mm) ~ Max 0.008" (0.2 mm)
	Label Roll Diameter	Max 5" (127 mm)
Core Diameter		1" (25.4 mm) , 1.5" (38.1 mm)
Printer Language		EZPL, GEPL, GZPL Auto Switch
Interface		USB 2.0 / Serial Port: RS-232 (DB-9) / IEEE 802.3 10/100 Base-Tx Ethernet port (RJ-45)
Control Panel		One Tri-color LED: Power (Green, Orange, and Red) / Function Key: FEED
Power		Auto Switching 100-240V AC, 50-60Hz
Real Time Clock		Standard
Environment	Operating Temperature	41° F to 104° F / 5° C to 40° C
	Storage Temperature	-4° F to 122° F / -20° C to 50° C
Humidity	Operation	30 - 85%, non-condensing
	Storage	10 - 90%, non-condensing
Approvals		CE (EMC), FCC Class A, CB, cUL and CCC
Dimension		6.53" / 166 mm
Weight		2.65 lbs / 1.2 kg
Options & Accessories		Label Dispenser, Print Head, Labels

Works with the S2000 Jr Price Computing Scales



Label Samples

Labels shown not to scale

Thank You		
Weight	Unit Price(\$/lb)	Total (\$)Price
10.00 lb	5.99	59.90
Have a nice day!		

▲ LST-8000B using DT2X
Standard Format

CAS Thank You :)		
Weight	Unit Price(\$/lb)	Total (\$)Price
3.6oz	8.99	32.36
99 Murray Hill Pkwy East Rutherford NJ 07073		

▲ Customized LST-8000B Label

CAS

99 Murray Hill Parkway
East Rutherford, NJ 07073
TEL: (201) 933-9002
FAX: (201) 933-9025
<http://www.cas-usa.com>

Specifications are subject to change for improvement without prior notice.