

Universal Stacking kit.



Combi-Duo Electric Universal Stacking kit on Stand I or Mobile Roller Kit. To provide the possibility to add other equipment with a max load of 551 lbs (250 kg) on top of the RATIONAL unit.

1



Half-Size

G	60.75.751	Universal Stacking Kit Gas
I	60.75.755	Universal Stacking Kit Electric

Mobile kit – Half-Size

Kit with height-adjustable rollers. Surface height with 6-half size (38 7/8" (989 mm)) or 10-half size (49 1/8" (1,249 mm)) Height adjustment by up to 3/4 in (20 mm); three settings.



60.31.622	Sizes 6-half size, 10-half size, dimensions W D H: 37 2/7 25 3 1/8 in (948 634 80 mm)
-----------	---

Stand I – Half-Size

Open on all sides. Surface height with 6-half size (43 1/2" (1,104 mm)) or 10-half size (53 5/8" (1,364 mm))



60.31.200	Standard, dimensions W D H: 33 7/8 27 7 7/8 in (860 685 200 mm)
60.31.201	With height-adjustable casters, dimensions W D H: 34 3/4 30 7 7/8 in (884 763 200 mm)
60.31.202	With anchoring (MarineLine), dimensions W D H: 34 7/8 28 7 7/8 in (885 710 200 mm)

2



Full-Size

H	60.75.752	Universal Stacking Kit Gas
J	60.75.756	Universal Stacking Kit Electric

Mobile kit – Full-Size

Kit with height-adjustable rollers. Surface height with 6-full size (38 7/8" (989 mm)) or 10-full size (49 1/8" (1,249 mm)) Height adjustment by up to 3/4 in (20 mm); three settings.



60.31.635	Sizes 6-full size, 10-full size dimensions W D H: 46 32 5/6 3 1/8 in (1170 834 80 mm)
-----------	---

Stand I – Full-Size

Open on all sides. Surface height with 6-full size (43 1/2" (1,104 mm)) or 10-full size (53 5/8" (1,364 mm))



60.31.203	Standard, dimensions W D H: 42 5/8 34 7/8 7 7/8 in (1082 885 200 mm)
60.31.204	With height-adjustable casters, dimensions W D H: 43 1/2 37 7/8 7 7/8 in (1106 963 200 mm)
60.31.205	With anchoring (MarineLine), dimensions W D H: 43 5/8 35 7/8 7 7/8 in (1107 910 200 mm)

1 iCombi Pro 6-half size, electric 2 iCombi Pro 6-full size, gas