



DESSERT & SALAD UNIT

MODEL RF-525

Refrigerated at 2 levels



For easy handling of 18" x 26" sheet pans

- Refrigerated surfaces at table height—and on overhead area
- Handy storage back-up cabinet holds up to 18 pans 2 1/4 inches apart
- Self closing doors with lock • Automatic defrost • Styrofoam insulation

Available any width, length and height as desired



CADDY CORPORATION OF AMERICA
SUBSIDIARY SUN WAVE U.S.A. CO. LTD.



SPECIFICATIONS

RF-525 Dessert and Salad Unit as manufactured by Caddy Corporation of America to be 88" long (additional lengths can be specified) × 36½" wide × 65¾" high, consisting of two independently controlled refrigeration systems, one for frost top and cold pan at 0° F. and one for storage base at 36° F. Condensate evaporator to be provided for base while frost top and cold pan to drain to manual valve mounted outside compressor housing. Frost top refrigerated unit to accommodate on top three (3) 18" × 26" sheet pans. Unit shall have continuous stainless steel top and base enclosed on all sides with stainless steel panels. Interior two compartments completely lined with stainless steel with pan slides 2¼" apart for up to 9 pans, capacity as

backup storage in each compartment. Refrigerated frost top overshef shall be 4⅝" high and designed to accept standard size dishes for salads and desserts, or the standard 18" × 26" pans. Unit shall have an interliner of #18 gauge stainless steel, one piece all welded construction. All corners shall be covered with a minimum of ¼" radius. Unit to have two vertical supports made of 1½" O.D. stainless steel tubing, insulated to prevent condensation. Unit mounted on 6 heavy duty 5" casters, all with brakes. One end to accept duplex receptacle and compressor housing with ¾ horsepower, 120 volt, 60 cycle, single phase compressor system, prewired with 6'-0" long 30 amp. cord and plug, NEMA #5-30 P.

