

### T-305 specifications:

Frame to be 1" O.D. 16 gauge stainless steel tubular construction. Casters to be 4" diameter heavy-duty swivel type with 3/4" stems and polyurethane tires.

Shelves to be of 12 gauge stainless steel entirely welded seamlessly with cutouts. Shelf corners shaped to fit contour of tubular frame and continuously welded to each leg at all contact points, which eliminates unsanitary crevices. Bottom shelf to be 15" above the floor and upper shelf to be 28" above the floor. Unit to be furnished with eight removable pans. Pans to be seamless 304 type stainless with No. 4 finish. Each pan to measure 11-1/2" x 6" x 6" deep.

Unit to be provided with the following accessories:

# Accessories

ACC-42 - Top and Bottom Shelf Covers to each be
provided with a double hinged fiberglass folding cover
with lock and key. Hinges to be 16 gauge stainless steel.
Locks to be chrome plated brass.
<b>ACC-38</b> - Circular bumpers. (Add 4" to length and width)

ACC-41 - Caster brakes on two diagonal casters.

ACC-47\* - Vinyl Drape

### T-407 specifications:

Frame to be of 1" O.D. 16 gauge stainless steel. Casters to be 4" diameter heavy-duty swivel type with 3/4" stems and polyurethane tires.

Shelves to be 16 gauge stainless steel with raised rounded edges on all sides, flanged down to form a 1-1/2" wide channel. Bottom shelf to be 12-1/2" from floor with 14-5/8" clearance between shelves. Shelf corners shaped to fit contour of tubular frame and continuously welded to each leg at all contact points, which eliminates unsanitary crevices. Each shelf to have 15 die-stamped reinforced openings for standard perforated plastic cutlery cylinders.

Unit to be provided with the following accessories:

# Accessories

ACC-49\*\* - Perforated plastic cutlery cylinders. Approximate capacity per cylinder: 48 knives, 36 forks, or 40 spoons.

ACC-41 - Caster brakes on two diagonal casters.

ACC-38 - Circular bumpers. (Add 4" to length and width)

ACC-47\* - Vinyl Drape

\* Specify model # T-305 or T-407 \*\* Specify quantity required

## CADDY CORPORATION

509 Sharptown Road P.O. Box 345 Bridgeport, NJ 08014-0345 Tel: 856-467-4222 Fax: 856-467-5511 internet: www.caddycorp.com

\* Specify model # T-305 or T-407