



# POWER PACK - WATER COOLED

PREMIUM - 3 PUMP - 11,500 BTUs


- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Anti-vibration pads reduce motor noise.
- Exterior sight glass to verify glycol bath level.
- Rugged stainless steel cabinet.



## **MMPP4307-PKG-3-WC**

Water Cooled:

Designed for spaces with limited air circulation or high ambient temperature.



**6-20P\***



\*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.



Part No.	Description	Shipping Weight
<input type="checkbox"/> MMPP4307-PKG-3-WC	Water cooled power pack, 3 pump and motor	134 kg
		295 lbs

**Operating Performance**

<b>Compressor</b>	1 1/2 HP	<b>Condenser Inlet Water Temp</b>	Minimum 45° F / Maximum 80° F
<b>BTU per hour</b>	11,500	<b>Pump Motor</b>	1/3 HP
<b>Plug Type (NEMA #)</b>	6-20P*	<b>Pump Type</b>	Rotary Vane
<b>Cord Length</b>	8'	<b>Push In Connector</b>	12.7mm (1/2") O.D.
<b>Voltage</b>	208/230	<b>Water Inlet &amp; Outlet Fitting</b>	Female 3/8" NPT
<b>Running</b>	11.4A	<b>Minimum Water Pipe Size</b>	3/8"
<b>Refrigerant</b>	R-404A	<b>Inlet Water Pressure</b>	Minimum 40 psi / Maximum 120 psi
<b>Charge</b>	1.04 kg (37 oz)	<b>Water Usage</b>	.98 GPM. Water is only used when the temperature of the condenser rises high enough to open the cooling inlet valve. This is approximately 40% of the operating time depending on ambient temperature and usage.
<b>Refrigerant Running Pressure</b>	55 (low) 260 (high)		
<b>Bath Capacity</b>	43.5 litre (11.5 gallons)		

\*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.

**Dimensions**

