

SBC58BLBIADANK



32.25" x 23.63" x 23.5" (H x W x D)

Built-in undercounter ADA height commercially listed beer dispenser with stainless steel wrapped door and black cabinet; no tapping equipment included

Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Built-in capable	Front-breathing design allows fully recessed installation under counters
Designed for 1/6 kegs	Interior can store up to two sixtel kegs
Tap kit not included	Install your own tapping equipment to create a customized beer cooler
Stainless steel wrapped door	304 grade stainless steel for a professional look with lasting durability
Professional handle	Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally
Adjustable thermostat	Interior dial thermostat ensures easy temperature management
Automatic defrost	No-frost operation for minimum user maintenance







SBC58BLBIADANK Specifications:

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatio
Door	Stainless Stee
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	110.0 lbs. (50 kg)
Shipping Weight	120.0 lbs. (54 kg)
Estimated Time to Ship	3 to 5 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Kegerator	
Door Swing	RHD
Reversible	Yes
Thermostat Type	Dia
Interior Light	Yes
Fan Type	Exterio
Refrigerant	R600a
Refrigerant Amount	0.64 oz
High Side PSI	180.0
Low Side PSI	80.0
Inter Height	25.75" (65 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF

