

## **SBC58WHBIADANK**



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed kegerator in white with stainless steel handle; no tapping equipment included

## **Highlights:**

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

## **Product Features:**

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Tap kit not included	Install your own tapping equipment to create a customized beer cooler	
White exterior finish	Classic and clean look suits any setting	
Professional handle	Solid tube style handle in brushed stainless steel offers a modern accent to the white door finish	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	
Automatic defrost	No-frost operation for minimum user maintenance	
Stainless steel drip tray	Removable two-piece drip tray included for added convenience	







## **SBC58WHBIADANK Specifications:**

Overview	
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Width	23.63" (60 cm)
Depth	22.75" (58 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatio
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Shipping Weight	110.0 lbs. (50 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101086514
Kegerator	
Door Swing	RHD
Reversible	Factory Reversible
Thermostat Type	Dia
Interior Light	Yes
Fan Type	Exterio
Refrigerant	R600a
Refrigerant Amount	0.64 oz
High Side PSI	180.0
Low Side PSI	80.0
Inter Height	25.75" (65 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF

