

Installation Kit

Article no. 8720.1560US

The RATIONAL Installation Kit ensures that the installer has all the essential connection materials on hand at the time of install. Not all parts are used in every installation.

Gas RATIONAL Combi Oven 6-half size G (120v/60/1ph) or (208v/60/1ph) Gas RATIONAL Combi Oven 10-half size G (120v/60/1ph) or (208v/60/1ph) Gas RATIONAL Combi Oven 6-full size (208-240v/60/1ph)

The Installation Kit for the above models includes:

1	ea	Gas Connector Hose, 3/4" NPT connection, 48" long, stainless steel braid with Plastic coat exterior, brass push to connect quick disconnect coupling, for castered equipment with cable strain relief
1	ea	90 degree black iron elbows, 3/4" NPT
2	ea	90 degree black iron street elbows, 1" NPT
1	ea	18" long × 3/4" NPT black iron pipe
1	ea	10" long × 3/4" NPT black iron pipe
1	ea	8" long × 3/4" NPT black iron pipe
1	ea	Close nipple 3/4" NPT black iron pipe
2	ea	45 degree black iron elbows, 3/4" NPT
2	ea	2" Minnies
1	ea	3/4" minnies
2	ea	3/4" Water Connector Hose, $5/8$ " ID, $3/4$ " female hose thread both ends, 60 " long rubber coated, NSF approved
1	ea	Male union 3/4" × 3/4" MHT
2	ea	90 deg Fresh water elbow
8	feet	2" copper pipe (two 4' pieces)
2	ea	2" copper pipe 90 degree elbow
1	ea	2" copper pipe T fitting
2	ea	2" copper pipe 45 degree elbow
1	ea	2" copper pipe 90 degree elbow female to male
1	ea	2" copper pipe 90 degree long sweep
1	ea	2" copper pipe coupling
1	ea	Receptacle NEMA 6-15R 15A-250V
1	ea	NEMA 6-15R cover plate single junction box
1	ea	NEMA 6-15P
1	ea	NEMA 5-15P

Please note that installation kits are non-discountable.