TES

Drawn:

GEF

Checked:

DMH

Approved:

JHB

Date:

T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690 Model No.

EC-3100-LN

Item No.

Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com

	This Space for Architect/Engineer Approval			neer Approval
	16.1	Job Name		Date
	ADA Compliant	Model Specifi	ed	Quantity
		Customer/Wh	olesaler	
	ChekPoint*	Contractor		
0.4/4		Architect/Engi	ineer	
2 1/4" [56mm] 2 1/2" [63mm]	3 5/8" x 4 3/16" x 2" Dee [92mm x 106mm x 51mi Water Resistant Control w/ Internal Flow Control AC or DC operated w/ (4 Hardwire Capable using	n] Module Box Setting Swit 1) AA Batteri	ches, ´ es.	
3/8" NPT Female Outlet	—24" [610mm] Sensor Cable —Removable Strainer	Mounting Surface		2 1/4" [58mm]
1/2" NPSM x 1/4" NPSM— 18" [457mm] Long Flexible Stainless Steel Hose		2 1/4" [57mm] _ Maximum Fhickness		Ø 1/8" [3mm] Anti-rotation Pin. Remove Pin if Desired. (See Mounting Hole Detail)
	W/ 14 Doub (Rem on M	240 VAC Ada 4" [3658mm le Power Co love Rubber odule and Connect)	l] Long ord. Plugs	Mounting Hole Detail Ø1" [25mm] Ø5/32"
Temperature Mixing Valve with Integral Check Valves			1/2" NPSM tainless Steel	1" [25mm]
Product Specifications:			Product Compliance:	
Chrome Plated Brass Electronic Faucet: Deck Mount (Less Gooseneck and Aerator), AC/DC Control Module with Internal Flow Control Setting Switches, Temperature Control Mixing Valve, 18" Long Hot & Cold Supply Stop Flexible Connector Hoses			ASME A112.18.1 / CSA B125.1 NSF 61 - Section 9 NSF 372 (Low Lead Content) ANSI A117.1 (ADA)	

UL 1951

Scale:

1:6

Sheet: 1 of

05/07/14



T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690

Model No.

EC-3100-LN

Item No.

Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com

	L		
SALES NUMBER	DESCRIPTION		
017195-45	Angled Sensor w/ Cable		
016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F		
016647-45	ChekPoint Module (Blue)		
5EF-0002	A/C Transformer		
5EF-0006	Mechanical Mixing Valve		
5EF-0005	Supply Hose, 9/16-24 Female x 1/2" NPSM		
EC-FILTER	Replacement Filter		
	017195-45 016297-45 016647-45 5EF-0002 5EF-0006 5EF-0005		



A Maximum of (8) ChekPoint Faucets can be Hardwire Connected and Powered by EC-HARDWIRE ChekPoint Hardwire AČ Transformer. (Sold Separately)

Label for Flow Control Switch Settings is Located on Inside of Back Cover.

Flow Control Switches are Located Inside Module Housing in Black Box Next to Battery Compartment.
*Switches are Set to DEFAULT Position:

- Auto Time Out = 15 Seconds
- Shut Off Delay = 1 Second
- Auto Flush = ÓFF

Remove (4) Screws and Back Cover to Access Switches.

*Available Water Flow Control Selections:

- Auto Time Out: 15 sec, 30 sec, 45 sec, 60 sec, 3 min, 20 min
- Shut Off Delay: 1 sec, 10 sec, 15 sec, 30 sec
- Auto Flush (30 Seconds After Every 12 Inactive Hours): ON or OFF

Product Specifications:

Chrome Plated Brass Electronic Faucet: Deck Mount (Less Gooseneck and Aerator), AC/DC Control Module with Internal Flow Control Setting Switches, Temperature Control Mixing Valve, 18" Long Hot & Cold Supply Stop Flexible Connector Hoses

Product Compliance:

ASME A112.18.1 / CSA B125.1 NSF 61 - Section 9 NSF 372 (Low Lead Content) ANSI A117.1 (ADA) UL 1951

Drawn: **GEF** Checked: DMH Approved: JHB Date: 05/07/14 Scale: NTS Sheet: 2 of 2