

JOB:	
ITEM NO:	

# SUPER DUTY ANGLE LEDGE UTILITY RACK 207-1820-SD

## **FEATURES AND BENEFITS:**

- Super duty utility rack for transport and storage of products on 18" x 26" pans and 14" x 18" trays.
- Fully welded framework of structural aluminum extrusions for rigidity and durability. Reinforced for rough handling.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Extruded angle ledge pan supports. Each is welded in place to withstand heavier loads.
   Bottom of pan or tray rests on angle ledges.
   See reverse side for capacity and pan spacing.
- Heavy duty 5" swivel casters, two with brakes.
   Provides mobility when fully loaded.



207-1820-SD





# ACCESSORIES and OPTIONS (Available at extra cost):

- ☐ Pan Stop
- □ Corner Bumpers
- □ Vertical Bumpers
- □ Perimeter Bumper
- □ Various Caster Options

See page G-36 for accessory details.

### 207-1820-SD Series







CRES COR	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT
MODEL NO.	CAP	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		ACT.
207-1820-SD	20	18 x 26	IN	22	29-5/8	69-3/4	18-3/8	28-7/8	61-1/2	LBS	75
		460 x 660	MM	560	755	1775	470	735	1565	KG	34

When ordering bumpers, add 2" to overall dimensions.

ALL ALUMINUM CONSTRUCTION IS WELDED AND FINISHED.

#### **RACK:**

- Posts: Extruded channels, 1-1/16 x 2 x .125.
- Top and bottom: Extruded channels, 1-1/16 x 2-3/8 x .188; welded to posts.
- Super Duty Tie Bars (2): Welded to front and back.
- Super Duty Extruded Channels (2): Welded at top.
- Casters: 5" dia., swivel, modulus tires, 1-1/4 wide, load cap. 250 lbs. each, temp. range -4°/+140°F.
   Sealed bearings. Two casters equipped with brakes.

#### **PAN SLIDES:**

 Extruded angles, 1-7/16 x 1-7/8 x .102; welded to posts on 3" centers.



Gold indicates our Best Rack with the best warranty in the industry.

3-Year Parts / 1-Year Labor with lifetime guarantee against rust & corrosion

### SHORT FORM SPECIFICATIONS

ERES COR®
5925 Heisley Road • Mentor, OH 44060-1833
Phone: 877/CRESCOR • Fax: 440/350-7267
www.crescor.com

In line with its policy to continually improve its products, CRES COR reserves the right to change materials and specifications without notice.