Grooved Cheese Blade (GCB)

BIZERBA

Bizerba GSP series slicers are certified to the current NSF/ANSI Standard 8-2018

... GSP HD i 90 -GCB series – automatic safety slicer ...

Award winning - safety illuminated dial!

- Variable 3-Speed, automatic drive system
- 3 Stroke Lengths, easily adapts to changing menu
- Energy Efficiency: Emotion intelligent motor control, motor adapts its performance to the resistance of the product, 255 r.p.m.
- High Yield: Operating time, designed for permanent operation, 24 hours
- High Yield: Unique carriage-shifting design allows for closer slicing resulting in the smallest remnant-end pieces, increased product yield
- High Yield: Food Fence holds product in place during automatic slicing, included
- High Yield: Product Deflector, magnetic lock, permanently mounted, included
- High Yield: Rear mounted, heavy-weighted lift arm with heavy duty meat grip, removable pusher plate, and remnant holder with 306 holding points, dish-machine safe
- High Yield: Food tray, GSP-TRAY-D, included
- High Yield: Widest product carriage for increased capacity
- · High Yield: Heavy-duty, 3 lb. blade knife cover
- High Yield: Precision machined pencil-point-groves on gauge plate, blade cover and carriage to reduce friction, better looking product
- Safety Interlock: Carriage Tilt and Gauge Plate lock, the cleaning process
- Safety Interlock: No-volt release
- · Safety Interlock: Shut off in slice thickness knob
- · Safety Interlock: Adjustable blade shut off settings: 15, 30, 45 seconds or turn-off
- Safety Interlock: Forced start with slice thickness knob below zero
- · Operator Safety: Slicer Installation, Start-up and Training, included
- · Operator Safety: Illuminated index slicing dial, at-a-glance machine status:
 - o green safe to unplug and safe for cleaning
 - $\circ\hspace{0.4cm}$ flashing red blade exposed, close gauge plate before cleaning
 - $\circ \hspace{0.1in}$ solid red proceed with caution, ready to slice
- Operator Safety: Green push-handle on carriage, safe slicing
- Operator Safety: Red remnant-lift arm handle, reminds operator to use caution
- Operator Safety: 3.5"W (90mm) x 9.13"H x 2.6"D thumb guard wall for maximum protection
- Operator Safety: 360° blade enclosure, no top-gaps in blade ring-guard
- Operator Safety: Zero blade exposure during the cleaning process
- Operator Safety: Front mounted controls
- Operator Safety: The ability to adjust both the speed and the stroke of the carriage "onthe-fly" will speed up your operation
- Operator Safety: Servo-motor provides assistance to operator by decreasing slicing effort, reduces operator fatigue during manual slicing mode
- Operator Safety: Low profile carriage for easy loading of heavy product
- Operator Safety: Side lift-arm for easy cleaning under slicer
- Food Safety: One piece anodized aluminum construction
- Food Safety: Non-removable carriage system for faster cleaning and sanitizing
- Food Safety: Double-sided seal between blade knife and housing, no gap for food to collect, better hygiene
- Food Safety: UL157 dairy grade seals and gaskets used to seal against water and food debris, no silicone used under seals, better hygiene
- · Food Safety: Liquid and debris diversion from all control surfaces
- Food Safety: Remote blade sharpener does not collect food debris during operation and is dishwasher safe for improved safety and hygiene, sharpener storage, included
- Food Safety: One piece carriage with seamless thumb guard for highest hygiene standards, no slotted-screw heads on thumb guard
- Food Safety: Enclosed base and under carriage, easy to clean, best hygiene
- One Year Warranty: On-site, labor and parts

Grooved Cheese Blade - Best blade in the industry


The unique design of our grooved chese blade produces clean and consistent slices. The hardness results in a long lasting sharp edge. The life of the blade is dramatically longer than the competition. Our standard blade is the hardest, thinnest, largest, straightest blade in the industry.

- 13" diameter, chromium coated hard alloy
- 60-62 Rockwell hardness at the edge



Gauge plate closed, safe to unplug for cleaning - green.









C.S.I. Division 11 | Section 4000

Model #: GSP HD i 90-GCB

Project Name:	AIA #
Location:	SIS #

Item Number: Quantity: _

Emotion(R) Technology -**Variable Frequency Drive Motor**

- 120 Volt
- 60 Hz | 1-phase AC current
- Frequency of nominal current 2.6 A
- Power consumption 0.240 kW
- Energy savings up to 60%
- Idle-running requires 45% less energy
- Stand-by mode 0.0 kW energy usage
- Cutting performance adapts to cutting resistance of the product
- · Less heating of machine, cooler food-zone surface

Blade diameter

• 13" (330 mm)

Blade speed

• 255 r.p.m.

Max. produce size

• Round: 7.95" (202 mm) • Height: 4.96" (126 mm) • Width: 11.42" (290 mm)

Strokes per minute

• Full: 30-40-50 Mid: 35-48-58 Short: 60-68-75

Slice thickness

0-0.94" (0-24 mm), infinitely variable

Thumb-guard rear wall

3.5"W x 11.13"H x 2.6"D (90 x 235 x 67 mm)

Gravity-feed slicing carriage

40° inclined gravity feed

- · Carriage height positioned towards center of blade

Noise control drive system

reduction in decibel pollution

Installation area

External dimensions

• (Lx W x H) 28.5" x 22.48" x

Operating area

- 31.5" (800mm)

Food Safety - Ingress Protection type


Weight of machine

122 lbs, 55 ka

- 32.5" x 27.8" x 32" (826 x 706 x 813 mm)

Additional equipment

- 350 mm), stomper weight is 3 lb (1.36 kg)
- 2.75" High Tall Product fence
- Equipment Stands
 - o SLICER-STAND-315
- 13" (330 mm) Grooved Cheese Blade (GCB)
- · Food tray, GSP-TRAY-D
- 4" high Leg set in lieu of side-lift-arm



H - Carriage inclination

- Carriage inclined 25° towards operator

• 61 dB level - a 20%

• (L x W) 20.94" x 17.48" (532 x 444 mm)

24.67" 724 x 571 x 627 mm)

- (L x W) 31.73" x 35.39" (806 x 899 mm)
- Recommended Above Floor Tabletop Height

• IP Solids level 3 | Liquids level 3

Shipping Details & Dimensions

- Total Shipping Dimensions (L x W x H):
- Total Shipping Weight: 150 lbs, 68 kg
- Cubic: Ft. 16.89, 0.48 m
- Density: 8.88 lb/cubic ft, 142.6 kg/cubic m

- Food Vegetable chute 7"dia x 12"L (178 x
- - o SLICER-STAND-275
- · Full Service Contracts, 1 to 60 months

W2 35.39" (899)

Members of the Bizerba Group

L1 19.17" (487)

L 28.5" (724) L2 31.73" (806)

Bizerba GmbH & Co. KG Wilhelm-Kraut-Straße 65 72336 Balingen Germany Tel. +49 7433 12-0 Fax +49 7433 12-2696 marketing@bizerba.de

www.bizerba.com

Bizerba USA Inc. 1804 Fashion Court Joppa, MD 21085

Tel. Office +1 732 565-6000 Tel. Service +1 732 565-6001 Fax +1 732 819-0429 us.foodservice@bizerba.com www.bizerba.com

6411 Edwards Blvd. Mississauga, Ontario L5T2PT Canada Tel. +1 888 240-3722 French Tel. +1 877 699-2199 Fax +1 905 816-0497 ca.info@bizerba.com

Bizerba Canada Inc.

www.bizerba.ca

Bizerba de México, S.A. de C.V. Av. Rio Mixcoac No. 157 Colonia Florida 01030 México, D.F. México Tel. +52 55 5663-1397 Fax +52 55 5663-1296 contacto@bizerba.com.mx www.bizerba.com.mx



BIZERBA



Food tray, GSP TRAY-D. included, GSP HD I 90 shown on optional SLICER-STAND-315.



Remote sharpener, better food safety

Closed base, easy to clean

Blade Sharpener Storage Kaddy GSP-BBS-KADDY, included





Warranty

The GSP HD Safety Slicer carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins with the date of purchase and, provided the unit is used properly in accordance with our instructions, is in full effect for one year from that date. Any work to be performed under this warranty must be performed between the hours of 8:00 a.m. and 4:30 p.m. local time, Monday to Friday. Bizerba will not pay overtime charges for work performed other than during normal business hours. Accessories have a 30-day replacement or repair warranty for the period beginning on the date of purchase. Damages incurred in transit or from installation error, accident, alteration or misuse are not covered. Transit damages should be reported to the carrier immediately. Bizerba shall not be liable for any consequential, compensatory, incidental, or special damages. All warranty work must be performed by a factory authorized Bizerba Representative.