

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Pass Thru Half Glass Door Heated Cabinet

Pass-Thru PRO Series

Model: PRO-77-6H-G-PT

___ FEATURES & BENEFITS =__

■ Digital temperature control & monitor system

- Keeps food products safe by maintaining constant temperatures
- · Alarm beeps when doors are not sealed
- · Early warning alarm program detects issues before malfunction occurs
- · Digital display allows for easy monitoring
- · Sensitive touch display

Ducted fan air distribution system

Maintains temperature within the food zone

On/Off switch

ON/OFF switch is located on control panel

All stainless steel cabinet construction

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ LED interior lighting

Includes a U.S. patented dimming option, exclusively from Turbo Air. This feature reduces energy consumption by 3~5%.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Half length glass doors with locks
- Self-closing doors with stay open feature at 120
- Heated cabinet holds 140°F ~ 180°F for the best in food preservation
- Lifetime guaranteed heavy duty hinges and handles














Pass-Thru PRO Series

(unit: inch)

Model: PRO-77-6H-G-PT

ELECTRICAL DATA		
Voltage	208~230V/115V/60Hz/1Ph	
Plug Type	NEMA L14-20P	
Full Load Amperes	15	
Wattage (W)	3000	
Cord Length (ft.)	8	
Refrigerant	R-290	
DIMENSIONAL DATA		
# of Doors	12	
# of Racks Accepted	3	
Net Capacity (cu. ft.)	78.1	
Ext. Length Overall (in.)	77 _{3/4} (1976mm)	
Ext. Depth Overall (in.)*	361/4 (920mm)	
Ext. Height Overall (in.)†	78 (1982mm)	
Int. Length Overall (in.)	681/4 (1735mm)	
Int. Depth Overall (in.)	275/8 (702mm)	
Int. Height Overall (in.)	583/4 (1493mm)	
# of Shelves	9	
Shelf Size (L x D) (in.)	223/4 x 263/8 (Left/Right)	
	25 x 263/8 (Middle)	
Net Weight (lbs.)	856	
Gross Weight (lbs.)	924	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty


STANDARD FEATURES


- Door locks
- 4" dia. swivel casters with locks on the front set
- · Easy replaceable one piece magnetic door gaskets
- · Solid and sturdy grille design

OPTIONAL ACCESSORIES

- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 4.7" leveling seismic leg (1/2", 13 TPI): 30221M0500
- 6" stainless steel leg: 30221M0600
- Additional stainless steel shelf: (L, R) H50R901700, (M) H77R801710
- Tray slides kits: TS23-N1LR(#1), TS23-N1LR HALF, TS23-N4LR(#4), TS23-N4LR HALF, TS23-UNLR-H(Universal), TS23-UNLR-H HALF, TS3-N1C(#1), TS3-N1C HALF, TS3-N4C(#4), TS3-N4C HALF, TS3-UNC-H(Universal), TS3-UNC-H HALF

PLAN VIEW





Ver 20230608















■ **Warranty**: 800-381-7770



■ **AC**: 888-900-1002

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

^{*} Depth does not include 2-1/2 for door handles.

[†] Height does not include 5" for caster height.