

FIVE STATION FLOOR MOUNTED SINK WITH TUBULAR LEGS & CROSS BRACING

KNEE OPERATED





Knee Valves Included On All "KV" Models

Item #:	_Qty #:
Model #:	
Project #:	





FEATURES:

8 1/2" high backsplash.

8" sink bowl depth.

Two stainless steel "Z" brackets.

Two K-6 3 1/2" rear basket drains.

Tubular stainless steel legs with flanged feet.

Side & rear adjustable cross-bracing with leg clamps.

Knee Operated: Includes five **7-PS-32** knee valves and five **K-121** spouts.

CONSTRUCTION:

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

MATERIAL:

All 16 gauge type "304" stainless steel.

1 5/8" tubular "304" stainless steel legs & cross-bracing. Stainless steel gussets.

MECHANICAL:

Single faucet hole punch at each station.

		# of	# of		Cu.
Model #	Length	Spouts	Knee Pedals	Wt.	Ft.
FC-FM-100KV	100"	5	5	185 Lbs.	35



MULTI-STATION ACCESSORIES & REPLACEMENT PARTS Model **Description** QTY: 7-PS-32 Knee Valve Assembly K-121 **K-6** 3 1/2" Drain (1 1/2" I.P.S.) **K-06** Splash Mount Faucet Mounting Kit Stainless Steel Soap Dispenser (Wall Mount Only) **K-13** K-411 **K-121** Single Hole, Splash Mounted 3-1/2" Gooseneck Spout Strainer Plate for 3-1/2" Drain **K-411** Special Sizing Charge (Larger Size TA-19 **K-508** Cut Down To Smaller Size) **TA-19** Adjustable Stainless Steel Flanged Bullet Foot

Ships UPS

Standard Faucets conform to NSF 61 Standard 9 and compliance to AB 1953 Standards.

MARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933 TOL ± .500" ALL DIMENSIONS ARE TYPICAL



