

. IIIII 1000 1000 1000 1000 1



## **Open Air Merchandisers**




- CFC free refrigerant and foam insulation
- Coated evaporator coil
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- White painted steel front and sides
- White polystyrene iinterior
- 3 Adjustable, heavy-duty epoxy coated wire shelves per door
- Magnetic door gasket is removable and replaceable without tools.
- Field reversible, lockable door with stainless steel handle.
- Larger fan motors and blades for more efficient air flow ensuring faster recovery times.
- Heating element built into condensate pan for efficient evaporation of excess water
- Bottom mounted compressor for more efficient operation in the coolest area of the kitchen.
- Easy to mount 3" casters (lockable in front) are standard with all units
- · Locking door on all units.
- Self contained capillary tube system using environmentally friendly CFC free refrigerant

(R404A in freezers and R134A in refrigerators).

- Tested to NSF Standard 7 requirements for open food storage.
- Electrical: 110/60/1 with NEMA 5-15P plug
- External Dimensions: 30.6" x 28.8" x 77.60" Internal Dimension: 26.3" x 22.8" x 65.4"

Warranty: 1-Year Parts & Labor, 5 Years on Compressor

MODEL	REFRIGERANT	TEMPERATURE	AMPS	H.P	BTU	SHIP WEIGHT
EKB25WF	R404A	0 to -10 (-17 to -23)	10.5	3/4	1966	269 lbs
EKB25WR	R134A	33 to 41 (0.5 to 5)	4.5	1/4	830	249 lbs







CERTIFIED TO ANSI/ NSF-7 STANDARDS