
TAG:	


# Easy Install Pre-Rinse Unit

## **Architect/Engineering Specifications:**

8" wall mount mixing faucet with polished chrome plated brass body, add-on faucet with compression cartridge and lever handle, 12" swing nozzle with stream regulator outlet, 18" riser, 44" flexible stainless steel hose with heat resistant handle, 1.42 GPM spray valve, compression cartridges with spring checks, lever handles, 1/2" NPT female inlets, 6" adjustable wall bracket, spray valve holder and overhead spring. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 & NSF 372. EPAct 2005 compliant.

Job Name	
Model Specified	Quantity
Variations Specified	
Date	







#### Features & Benefits:

- 8" wall mount mixing faucet w/ polished chrome plated brass body
- EasyInstall add-on faucet w/ polished chrome plated brass body
- 12" swing nozzle w/ stream regulator outlet, Series 1
- 18" rigid riser
- 44" flexible stainless steel hose with heat resistant gray handle and hold down rina
- 1.42 GPM spray valve
- Quarter-turn Eterna compression cartridges with spring checks to prevent cross flow of water
- Lever handles w/ color coded indexes
- 1/2" NPT female eccentric inlets with Ø 2" flanges

Optional Add-On Faucet Outlets (Series 1 / VR Series 6)

- Adjustable centers from 7 3/4" to 8 1/4"
- 6" adjustable wall bracket

**Aerated** 

□ B-0199-01-F10

□ B-0199-01-WS

□ B-0199-01

Material: Polished chrome plated brass body, tubular nozzle, add-on faucet body, riser & spray valve body, stainless steel hose and chrome plated metal handles

VR Aerated

(VR Laminar)

□ B-0199-06

□ B-0199-06-F10

□ B-0199-06-WS

### **Product Compliance:**

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- EPAct 2005 (PRSV)

Warranty: Three Year (Limited)



#### **Performance Data:**

Pressure: 20 - 125 psi Temperature: 40 °F - 140 °F

Flow Rate:

Spray Valve: 1.42 GPM @ 60 psi Add-On Faucet: 9.73 GPM @ 60 psi

#### **Optional Cartridges With Checks**

- □ Quarter-Turn Cerama w/ Check Valve
- ☐ Quarter-Turn Eterna w/ Spring Check (Standard)

## □ Lever (Standard)

□ 4-Arm

**Optional Handles** 

☐ 4" Wrist Action

## **Optional Pre-Rinse Spray Valves**

- ☐ B-0107 (1.42 GPM)(Standard)
- □ B-0107-C (0.65 GPM)
- □ B-0107-J (1.07 GPM)
- □ B-0108 (1.07 GPM)
  □ B-0108-C (0.65 GPM)



**GPM** 

1.0

1.5

2.2







