

**Architect/Engineering Specifications:**

Repair parts for standard type T&S spray valve. Certified to NSF 61–Section 9 and NSF 372. EPAAct 2005 compliant.

Job Name \_\_\_\_\_  
 Model Specified \_\_\_\_\_ Quantity \_\_\_\_\_  
 Variations Specified \_\_\_\_\_  
 Date \_\_\_\_\_



000895-45  
Spring  
Qty. = 2



000974-45  
Bonnet  
Washer (Brass)  
Qty. = 2




001100-45  
Packing  
Seal  
Qty. = 2



010476-45  
#27 Hose  
Washer  
Qty. = 2



012915-45  
Seat  
Washer  
(New Style)  
Qty. = 2



001040-45  
Bonnet  
Binding  
Washer  
Qty. = 2



007861-45  
B-0107 Sprayhead  
Ring  
Qty. = 1



001121-45  
B-0107 Spray Face  
Qty. = 1



000913-45  
Spray Face  
Screw  
Qty. = 1



009306-20  
Valve  
Stem  
Qty. = 2

**Features & Benefits:**

- Valve stem, spring, washers and packing seal
- Spray face and components to ensure GPM output accuracy
- Material: Brass valve stem and plastic spray face

**Product Compliance:**

- NSF 61 - Section 9
- NSF 372 (Low Lead Content)
- EPAAct 2005 (PRSV)



**Warranty:** One Year (Limited)

**Performance Data:**

- Flow Rate: 1.42 GPM @ 60 psi

