



To whom it may concern:

Electrolux Professional builds and promotes high-end reliable equipment such as our SkyLine and MultiSlim combi ovens. Our combi ovens are designed and manufactured to withstand long hours of operation when properly installed and subsequently maintained.

Correct installation and maintenance are key factors for reliable equipment operation during its lifetime. Electrolux Professional has included an *Automatic Cleaning System* and a *Reverse Osmosis System* to protect the customer's investment. The *Automatic Cleaning System* removes cooking grease residuals, and automatically descales the combi oven boiler. The *Reverse Osmosis System* protects the equipment from corrosive water or hard water.

In the event a customer decides against the Electrolux Professional Reverse Osmosis System the customer assumes full responsibility of meeting the combi oven water supply specifications as listed below.

Water:	
Water inlet "FCW" connection:	3/4"
Pressure:	15-65 psi (1-4.5 bar)
Drain "D":	2" (50 mm)
Max inlet water supply temperature:	86°F (30°C)
Chlorides:	<17 ppm
Conductivity:	>285 µS/cm
Water drain outlet:	1 15/16" (50mm)
Water inlet cold 1:	3/4"
Water inlet cold 2:	1/2"
Electrolux recommends the use of treated water, based on testing of specific water conditions.	
Please refer to user manual for detailed water quality information.	

Failing to supply our combi oven with water meeting the spec above may result in damage to the equipment that will not be covered by product warranty.

ELECTROLUX PROFESSIONAL